



## N BULKHEAD JACKS

| Cable<br>RG-/U           | Conn.<br>Type | Cable Attachment |        | Dimensions, inches (millimeters) |            |            |            |            | Notes |      |      | Mtg<br>Hole | Military<br>Number | Amphenol<br>Number | Fig |
|--------------------------|---------------|------------------|--------|----------------------------------|------------|------------|------------|------------|-------|------|------|-------------|--------------------|--------------------|-----|
|                          |               | Outer            | Inner  | a                                | b          | c ?        | d          | e          | CAI   | Plt. | Ins. |             |                    |                    |     |
| 55, 58, 141,<br>142, 223 | Bulkh.        | Clamp            | Solder | 1.67(42.5)                       | .813(20.6) | .224(5.7)  | .910(23.1) | .317(8.1)  | C8    | P1   | D1   | U           | UG-556B/U          | 35275              | 1   |
| 55, 142, 223             | Bulkh.        | Crimp            | Crimp  | 1.73(43.9)*                      | .872(22.1) | .220(5.6)  | .935(23.7) | .250(6.4)  | C11   | P15  | D1   | U           | —                  | 82-5373            | 2   |
| 188, 316                 | Bulkh.        | Solder           | Crimp  | 1.59(40.4)*                      | .866(22.0) | .178(4.5)  | .917(23.3) | .315(8.0)  | C11   | P15  | D9   | U           | —                  | 82-5933            | 3   |
| 58, 141                  | Bulkh.        | Crimp            | Crimp  | 1.74(44.2)*                      | .872(22.1) | .206(5.2)  | .926(23.5) | .250(6.4)  | C11   | P34  | D1   | U           | —                  | 82-5378            | 4   |
| LMR 600                  | Bulkh.        | Crimp            | Crimp  | 2.21(56.1)*                      | .933(23.7) | .625(15.9) | .926(23.5) | .250(6.4)  | C11   | P34  | D9   | U           | —                  | 82-5994            | 5   |
| LMR 240, 8X              | Bulkh.        | Crimp            | Crimp  | 1.41(36.0)*                      | .866(22.0) | .259(6.6)  | .866(22.0) | .255(6.5)  | C11   | P7   | D1   | —           | —                  | 82-6151            | 6   |
| 174, 188, 316            | Bulkh.        | Crimp            | Crimp  | 1.53(39.0)*                      | .866(22.0) | .133(3.4)  | .866(22.0) | .255(6.5)  | C11   | P7   | D1   | —           | —                  | 82-6156            | 7   |
| LMR 400                  | Bulkh.        | Crimp            | Crimp  | 1.93(49.0)*                      | .750(19.0) | .420(10.6) | .917(23.2) | .324(8.22) | C11   | P34  | D9   | U           | —                  | 82-6143-1000       | 8   |