



# PRODUCT DATA SHEET

Controlled Document - Engineering Drive

1530 Shields Drive  
Waukegan, IL 60085  
Toll-Free (800) 323-9355  
Fax: (847) 689-1192

**PART NUMBER:** 18011  
**DESCRIPTION:** 10 AWG XHHW-2 CABLE  
**CONSTRUCTION:** This cable consists of one bare copper conductor with integral insulation and jacket.  
**APPROVALS:** UL Standard 44 and CSA 22.2 No. 38.  
**APPLICATION:** Thermoset Insulated Distribution Panel/Equipment Wiring Applications.

---

## Construction Parameters:

Conductor	10 AWG Bare Copper
Stranding	7/.0385"
Insulation Material	XLPE
Insulation Thickness	0.031" Nom.
Insulated Conductor Diameter	0.177" Nom.
Approximate Cable Weight	40.7 Lbs/1M' Nom.
Flame Rating	CSA FT1 Vertical Flame Test

---

## Electrical Properties:

Temperature Rating	-20°C to 90°C Dry/Wet
Operating Voltage	600 V RMS Max.
DC Resistance per Conductor @ 20°C	1.01 Ohms/1M' Nom.

---

Insulation/Jacket Color	Colors vary
-------------------------	-------------

Legend (Surface Ink Print)	CCI ROYAL 10 AWG (5.26mm <sup>2</sup> ) E137925 (UL) XHHW-2 90C 600V -- C(UL) RW90 XLPE 90C WET OR DRY 600V FT1
----------------------------	---

This product complies with European Directive 2002/95/EC (RoHS)  
On special orders, the customer will accept all factory lengths and +/- 10 percent of total order requested.

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Coleman Cable's control all product data presented is for informational purposes only and does not create a binding obligation or liability on Coleman Cable or confer any rights on any customer. The sale of products(s) is conditioned upon acceptance of a purchase order subject to Coleman Cable's standard terms and conditions contained therein, including without limitation Coleman Cable's standard warranty. Coleman cable disclaims all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Coleman Cable. Any information contained herein shall not be disclosed to any party without written consent of Coleman Cable.

Customer Name \_\_\_\_\_

Customer Approval \_\_\_\_\_

Specification Issue Date: June 10, 2010