

PRODUCT DATA SHEET

Controlled Document - Engineering Drive

1530 Shields Drive Waukegan, IL 60085 Toll-Free (800) 323-9355 Fax: (847) 689-1192

PART NUMBER: 18012

DESCRIPTION: 12 AWG XHHW-2 CABLE

CONSTRUCTION: This cable consists of one bare copper conductor with integral insulation and jacket.

APPROVALS: UL Standard 44 and CSA 22.2 No. 38.

APPLICATION: Thermoset Insulated Distribution Panel/Equipment Wiring Applications.

Con	struc	tion	Param	eters:

Conductor 12 AWG Bare Copper

Stranding 7/.0305"
Insulation Material XLPE
Insulation Thickness 0.031" Nom.
Insulated Conductor Diameter 0.154" Nom.
Approximate Cable Weight 28.1 Lbs/1M' Nom.

Flame Rating CSA FT1 Vertical Flame Test

Electrical Properties:

Temperature Rating
Operating Voltage

600 V RMS Max.

DC Resistance per Conductor @ 20^oC 1.60 Ohms/1M' Nom.

Insulation/Jacket Color Colors vary

Legend (Surface Ink Print) CCI ROYAL 12 AWG (3.309mm²) E137925 (UL) XHHW-2 90C 600V -- C(UL) RW90 XLPE 90C

WET OR DRY 600V FT1

This product complies with European Directive 2002/95/EC (RoHS)

On special orders, the customer will accept all factory lengths and +/- 10 percent of total order requested.

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Coleman Cable's control all product data presented is for informational purposes only and does not create a binding obligation or liability on Coleman Cable or confer any rights on any customer. The sale of products(s) is conditioned upon acceptance of a purchase order subject to Coleman Cable's standard terms and conditions contained therein, including without limitation Coleman Cable's standard warranty. Coleman cable disclaims all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Coleman Cable. Any information contained herein shall not be disclosed to any party without written consent of Coleman Cable.

Customer Name	
Customer Approval	

Specification Issue Date: April 27, 2010