



PRODUCT DATA SHEET

Controlled Document - Engineering Drive

1530 Shields Drive
Waukegan, IL 60085
Toll-Free (800) 323-9355
Fax: (847) 689-1192

PART NUMBER: 30200
DESCRIPTION: 8 AWG UL TYPE PPE CABLE
CONSTRUCTION: This cable consists of one bare copper conductor and TPE insulation and jacket.
APPROVALS: UL Type PPE, PPC/TPE CSA C22.2 No. 96, NEC Article 400., MSHA
APPLICATION: 2000V Portable Wet Rated Submersible Outdoor Flexible Power Cable

Construction Parameters:

Conductor	8 AWG Bare Copper
Stranding	7x24/30
Insulation Material	PVC
Insulation Thickness	0.062" Nom.
Insulated Conductor Diameter	0.277" Nom.
Number of Conductors	1
Jacket Reinforcement	Nylon Mesh Braid
Jacket Material	PVC
Jacket Thickness	0.077" Nom.
Overall Cable Diameter	0.431" Nom.
Approximate Cable Weight	127.9 Lbs/1M' Nom.
Flame Rating	UL/CSA Horizontal Flame Test

Electrical Properties:

Temperature Rating	-50°C to 90°C Dry, 75°C Wet
Operating Voltage	2000V RMS Max.
DC Resistance per Conductor @ 20°C	0.775 Ohms/1M' Nom.
Max Ampacity per Conductor (Per NEC Table 400-5b)	80 amps/cond (Assume one current carrying conductor in free air)

Insulation Colors	Black
Jacket Color	Black

Legend (Indent)	CCI SEOPRENE 8 AWG TYPE PPE E172226 (UL) 600/2KV 90C DRY 75C WET SUNLIGHT RESISTANT P-241-3-MSHA
-----------------	---

This product complies with European Directive 2002/95/EC (RoHS)

Note: Type PPE cable is identical to Type W cable except it has TPE insulation and jacket.

Packaging will be Coleman's standard wooden reels with shrink-wrap over the cable.

On special orders, the customer will accept all factory lengths and +/- 10 percent of total order requested.

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Coleman Cable's control all product data presented is for informational purposes only and does not create a binding obligation or liability on Coleman Cable or confer any rights on any customer. The sale of products(s) is conditioned upon acceptance of a purchase order subject to Coleman Cable's standard terms and conditions contained therein, including without limitation Coleman Cable's standard warranty. Coleman cable disclaims all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Coleman Cable. Any information contained herein shall not be disclosed to any party without written consent of Coleman Cable.

Specification Issue Date: August 28, 2012