

PRODUCT DATA SHEET

Controlled Document - Engineering Drive

1530 Shields Drive Waukegan, IL 60085 Toll-Free (800) 323-9355 Fax: (847) 689-1192

PART NUMBER: 61008

DESCRIPTION: 12/10 COMPACT 600 TRAY CABLE

CONSTRUCTION: This cable consists of ten bare copper insulated conductors cabled with a reinforced mylar wrap

and an oil and sunlight resistant overall jacket.

APPROVALS: UL Standard 1277, NEC Article 340.

600 Volt Power and Control Tray Cable

Construction Parameters:

Conductor 12 AWG Bare Copper

Stranding 65/30
Insulation Material PVC/Nylon
Insulation Thickness 0.021" Nom.
Insulated Conductor Diameter 0.135" Nom.
Number of Conductors 10
Lay Length 5.00" Nom.

Filler Type Dry Jute
Separator/Wrap Reinforced Mylar
Jacket Material TPE
Jacket Thickness 0.065" Nom.

Overall Cable Diameter 0.690" Nom.
Approximate Cable Weight 324.1 Lbs/1M' Nom.

Flame Rating UL 1581 Vertical Tray Flame Test

Electrical Properties:

Temperature Rating -40°C to 90°C
Operating Voltage 300 V RMS Max.
DC Resistance per Conductor @ 20°C 1.59 Ohms/1M' Nom.

Insulation Colors Blk Red Blue Orange Yellow Brown Red/Black Blue/Black Orange/Black

Yellow/Black

Jacket Color Black (Other colors available for minimum order)

Legend (White Surface Ink Print) CCI 12-10 COMPACT 600V THHN/THWN (UL) TYPE TC 90C OIL RES I SUNLIGHT

RESISTANT

The customer will accept all factory lengths and +/- 10 percent of total order requested.

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Coleman Cable's control all product data presented is for informational purposes only and does not create a binding obligation or liability on Coleman Cable or confer any rights on any customer. The sale of products(s) is conditioned upon acceptance of a purchase order subject to Coleman Cable's standard terms and conditions contained therein, including without limitation Coleman Cable's standard warranty. Coleman Cable disclaims all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Coleman Cable. Any information contained herein shall not be disclosed to any party without written consent of Coleman Cable.

Specification Issue Date: January 10, 2014