



# PRODUCT DATA SHEET

Controlled Document - Engineering Drive

1530 Shields Drive  
Waukegan, IL 60085  
Toll-Free (800) 323-9355  
Fax: (847) 689-1192

**PART NUMBER:** 60126  
**DESCRIPTION:** 16/2 STRANDED TYPE SPT-2  
**CONSTRUCTION:** This cable consists of two bare copper conductors laid flat with integral insulation and jacket.  
**APPROVALS:** UL Standard 62, CSA 22.2 No. 49, NEC Article 400.  
**APPLICATION:** 300V Flexible Cable

---

## Construction Parameters:

Conductor	16 AWG Bare Copper
Stranding	26/30
Insulation Material	PVC
Insulation Thickness	0.048" Nom.
Insulated Conductor Diameter	0.155" x 0.303" Nom.
Number of Conductors	2
Approximate Cable Weight	36.0 Lbs/1M' Nom.
Flame Rating	UL/CSA Horizontal Flame Test

---

## Electrical Properties:

Temperature Rating	-20°C to 60°C
Operating Voltage	300 V RMS Max.
DC Resistance per Conductor @ 20°C	3.46 Ohms/1M' Nom.

---

Insulation/Jacket Colors	Black, Brown, White (Other colors available for minimum order - consult factory)
--------------------------	--

Legend (Indent Print)	E54864 * 16-2 SPT-2 (UL) -- CSA LL39753 * 16-2 SPT-2 60C FT2
-----------------------	--

This product complies with European Directive 2011/65/EU (RoHS-2)

On special orders, the customer will accept all factory lengths and +/- 10 percent of total order requested.

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Coleman Cable's control all product data presented is for informational purposes only and does not create a binding obligation or liability on Coleman Cable or confer any rights on any customer. The sale of products(s) is conditioned upon acceptance of a purchase order subject to Coleman Cable's standard terms and conditions contained therein, including without limitation Coleman Cable's standard warranty. Coleman Cable disclaims all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Coleman Cable. Any information contained herein shall not be disclosed to any party without written consent of Coleman Cable.

Specification Issue Date: January 14, 2013