



PRODUCT DATA SHEET

Controlled Document – Engineering Drive

1530 Shields Drive
Waukegan, IL 60085
Toll-Free (800) 323-9355
Fax: (847) 689-1192

PART NUMBER: 671803
DESCRIPTION: 18 AWG / 3 CONDUCTOR SHIELDED WITH JACKET
RATING: UL LISTED AS CM/CL2
UL RECOGNIZED COMPONENT AWM STYLE 2093

Construction Parameters:

	OD (in)*
Conductor: 18 AWG (16/30) Stranded Tinned Coated Copper	0.047
Dielectric: Polyethylene	0.081
Assembly & Shielding: 3 Conductors are stranded wrapped overall with Aluminum/Polyester tape with aluminum side out. A 20 AWG (10/30) Stranded Tinned Coated drain wire is added to the outside of tape.	0.180
Jacket: PVC	0.232

Miscellaneous Information:

Wire Colors:	Black Clear Red
Flame rating:	UL-1581 Vertical Tray Flame Test
Jacket Color:	Chrome Gray
Jacket Print (black):	CCI E100316 18 AWG TYPE CM/CL2 (UL) OR AWM STYLE 2093
Max. Operating Volts:	300
Max. Operating Temperature:	60° C
Applicable NEC Article:	725, 800 and 310
Approximate Weight (lb/1000 ft):	34

This product complies with European Directive 2002/95/EC (RoHS)

On special orders the customer will accept all factory lengths and ± 10% of total order requested.

The information presented here is, to the best of our knowledge, true and accurate. However, since conditions of use are beyond our control, all recommendations or suggestions are presented without guarantee or responsibility on our part. We reserve the right to review and modify all constructions to conform with the latest Regulatory requirement. We disclaim all liability in connection with the use of information contained herein or otherwise. This specification is propriety intellectual property of COLEMAN CABLE. Any information contained herein shall not be disclosed to any party without written consent of COLEMAN CABLE.

Issued: 1/10/14

* = Nominal value
By: PEP