

## PRODUCT DATA SHEET

Controlled Document - Engineering Drive

1530 Shields Drive Waukegan, IL 60085 Toll-Free (800) 323-9355 Fax: (847) 689-1192

**PART NUMBER:** 71704

DESCRIPTION: 16/4 STRANDED CL3P/CMP/FPLP FT6 PLENUM CABLE

**CONSTRUCTION:** This cable consists of four bare copper insulated conductors and an overall jacket.

UL Standard 13, 444 & 1424; NEC Articles 725, 760 & 800. APPROVALS:

Communications Cable, Class 3 Power Limited Circuit Cable and/or Fire Alarm Power APPLICATION:

Limited Circuit Cable used for Plenum Applications.

## **Construction Parameters:**

Conductor 16 AWG Bare Copper Stranding 19/.0117" Insulation Material Low Smoke PVC Insulation Thickness 0.006" Nom. 0.070" Nom. Insulated Conductor Diameter **Number of Conductors** 

Lay Length 5.00" Nom. Jacket Material Low Smoke PVC Jacket Thickness 0.017" Nom. Overall Cable Diameter 0.203" Nom. Approximate Cable Weight 46.1 Lbs/1M' Nom.

Flame Rating NFPA 262 Steiner Tunnel Smoke and Flame Test



**Cable Cross-Section** 

## **Electrical Properties:**

-20°C to 75°C Temperature Rating

300V Max per NEC Article 800 Operating Voltage

Capacitance Between Conductors @ 1 KHz 45 pF/ft Nom.

Capacitance Between Conductors to Shield @ 1 KHz

DC Resistance per Conductor @ 20°C 3.92 Ohms/1M' Nom.

Insulation Colors Black Red White Green

Jacket Color

Legend (Surface Ink Print) CCI 71704 16 AWG 4/C C(ETL) US (ETL CODE) TYPE CMP/CL3P/FPLP 75C --

TYPE CMP FT6

This product complies with European Directive 2002/95/EC (RoHS)

On special orders, the customer will accept all factory lengths and +/- 10 percent of total order requested.

Cable has a rip cord for easy jacket removal. The jacket is sequentially footmarked.

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Coleman Cable's control all product data presented is for informational purposes only and does not create a binding obligation or liability on Coleman Cable or confer any rights on any customer. The sale of products(s) is conditioned upon acceptance of a purchase order subject to Coleman Cable's standard terms and conditions contained therein, including without limitation Coleman Cable's standard warranty. Coleman Cable disclaims all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Coleman Cable. Any information contained herein shall not be disclosed to any party without written consent of Coleman Cable.

Specification Issue Date: December 5, 2013