



PRODUCT DATA SHEET

Controlled Document - Engineering Drive

1530 Shields Drive
Waukegan, IL 60085
Toll-Free (800) 323-9355
Fax: (847) 689-1192

PART NUMBER: 57506
DESCRIPTION: 8/2 W/Gnd 3/4" x 6' Air Conditioning Whip
CONSTRUCTION: This cable consists of three insulated conductors inserted into a non-metallic conduit with a straight metal connector on one end and a 90 degree metal connector on the other end.
APPROVALS: Underwriters Laboratory (UL) and c(UL)
APPLICATION: Connection between outside air conditioning unit and electrical power.

Construction Parameters:

Conductors	8 AWG Bare Copper
Ground	10 AWG Bare Copper
Stranding	19 Strand
Length of Conduit	6 feet +/- 2 inches.
Length of THHN	8 feet +/- 2 inches.
Trade Size of Conduit	3/4 Inch
Connector Type	1-Straight Metal 1-90 Degree Metal

Electrical & Environmental Properties:

Temperature Rating	-20°C to 90°C
Operating Voltage	600 Volts Max RMS
Ampacity	55 Amps per NEC Table 310-16 for 8ga THHN.

Insulation Colors	8ga: Black Red 10ga: Green
Conduit Color	Gray

Whip will be coiled and tied and placed in a bag.

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Coleman Cable's control all product data presented is for informational purposes only and does not create a binding obligation or liability on Coleman Cable or confer any rights on any customer. The sale of products(s) is conditioned upon acceptance of a purchase order subject to Coleman Cable's standard terms and conditions contained therein, including without limitation Coleman Cable's standard warranty. Coleman Cable disclaims all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Coleman Cable. Any information contained herein shall not be disclosed to any party without written consent of Coleman Cable.

Specification Issue Date: January 14, 2014