

PRODUCT SPECIFICATION

Controlled Document - Engineering Drive

CATALOG NUMB DESCRIPTI						
APPROVA	•		or Use Cord Set			
CONSTRUCTION PARAMETERS:						
Conductor:						
Cable jacke	•					
Overall cable O.D. (nom): Cord rating:						
Cable le	•					
						6/3 - 12/3
						10/3
Attachment plug configuration: NEMA 5-15P						
Cord connector configuration: NEMA 5-15R						
Plug and connector material: Clear PVC, with neon power indicator lamp in the cord connector						
ELECTRICAL AND ENVIRONMENTAL PROPERTIES:						
Cable temperature rating: -50 to +105 °C						
Nominal operating voltage: 125 VAC						
Maximum operating current: See table below						
Catalog no.	Gauge	Length	Conductor	Cable O.D.	Current rating	
01294	16/3	10 ft	26/30 BC	0.316 in	10.1	
01297 01298		25 ft 50 ft			13A	
01298		100 ft			10A	
01497	14/3	25 ft	41/30 BC	0.352 in		
01498		50 ft			15A	
01499		100 ft			13A	
01697	12/3	25 ft	65/30 BC	0.420 in		
01698		50 ft			15A	
01699 01798		100 ft 50 ft	104/30 BC	0.567 in	10A	
01799	10/3	100 ft				

This product complies with European Directive 2011/65/EU (RoHS-2)

The information presented here is, to the best of our knowledge, true and accurate. However, since conditions of use are beyond our control, all recommendations or suggestions are presented without guarantee or responsibility on our part. We disclaim all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Coleman Cable Inc. Any information contained herein shall not be disclosed to any party without written consent of Coleman Cable Inc.