

PRODUCT SPECIFICATION

Controlled Document - Engineering Drive

| CATALOG NUMBER: | See table below | | |
|----------------------------------------------------------------------------------------------|--------------------------------------------------------------------------|---------------------|---|
| DESCRIPTION: | POLAR/SOLAR Plus™ SEOOW extension cord with Quadnector [®] four | | |
| | outlet cord connector with power indicator light | | |
| APPROVALS: | | Jse Indoor Cord Set | 5 |
| CONSTRUCTION PARAMETERS: | | | |
| Gauge: 12/3 | | | |
| Conductor: 65/30 BC | | | |
| Cable jacket material: TPE, yellow | | | |
| Overall cable O.D. (nom): 0.585 in | | | |
| Cord rating: Extra Hard Usage per the National Electrical Code | | | |
| Cable legend type: Indent print | | | |
| | 38 | | |
| | 36 | | |
| Attachment plug configuration: NEMA 5-15P | | | |
| Cord connector configuration: NEMA 5-15R x 4 | | | |
| Plug and connector material: Clear PVC, with neon power indicator lamp in the cord connector | | | |
| ELECTRICAL AND ENVIRONMENTAL PROPERTIES: | | | |
| Cable temperature rating: -50 to +105 °C | | | |
| Nominal operating voltage: 125 VAC | | | |
| Maximum operating current: 15A | | | |
| | Catalog no. | Length | |
| | 04522 | 6 ft | |
| | 04527 | 25 ft | |
| | 04528 | 50 ft | |
| | 04529 | 100 ft | |

This product complies with European Directive 2011/65/EU (RoHS-2)

The information presented here is, to the best of our knowledge, true and accurate. However, since conditions of use are beyond our control, all recommendations or suggestions are presented without guarantee or responsibility on our part. We disclaim all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Coleman Cable Inc. Any information contained herein shall not be disclosed to any party without written consent of Coleman Cable Inc.