

PRODUCT SPECIFICATION

GENERAL INFORMATION:	
Catalog number: Se	ee table below
Description: 6/2	2 & 8/1 SRDT, 125/250V 50A range power supply cord
kit	with flanged spade terminals and metal strain relief
Approvals: UL	Listed
CONSTRUCTION PARAMETERS:	
Cable ty	/pe: SRDT, flat, gray
Insulation and jacket mater	rial: PVC, integral insulation and jacket
Conducto	ors: (2) 6 AWG & (1) 8 AWG, bare copper
Conductor identificati	ion: Center conductor (8 AWG neutral) is ribbed
Overall cable dimensions (no	om): 1.025 x 0.400"
Temperature rati	ing: -20 to +60 deg C
	17
	0. ES
Note: Plug style may vary	
Plug configurati	ion: NEMA 10-50P
Plug electrical ratin	ngs: 125/250 VAC, 50A
Plug mater	rial: PVC, gray
Termina	
Strain rel	lief: Metal, included but not attached
CATALOG NUMBERS:	
Ler	ngth Catalog number
	ft 09014
	5 ft 09015
6	6 ft 09016

The information presented here is, to the best of our knowledge, true and accurate. However, since conditions of use are beyond our control, all recommendations or suggestions are presented without guarantee or responsibility on our part. We disclaim all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Coleman Cable Inc. Any information contained herein shall not be disclosed to any party without the written consent of Coleman Cable Inc.

Coleman Cable Inc. 1530 Shields Drive, Waukegan, IL 60085 800.323.9355 www.colemancable.com