

## PRODUCT SPECIFICATION

**CATALOG NUMBER:** See table below

**DESCRIPTION:** 16/2 w/gnd SPT-3 replacement power supply cord **APPROVALS:** UL Listed and either CUL Listed or CSA Certified

## **CONSTRUCTION PARAMETERS:**

Conductor: 16 AWG, 26/30 bare copper

Conductor O.D. (nom): 0.059"
Insulated ground conductor O.D. (nom): 0.089"

Insulation material: PVC Insulation color: Gray

Overall cable dimensions (nom): 0.181 x 0.413"

Cord length: See table below

Attachment plug configuration: NEMA 5-15P, see table below for configuration

Plug material: PVC Plug color: Gray

Open end configuration: 1.5" separation, 0.38" strip

## **ELECTRICAL PROPERTIES:**

Temperature rating: -20 to +60 °C

Nominal operating voltage: 125 VAC
Maximum operating current: 13 A
Maximum operating wattage: 1625 W

## **CATALOG NUMBERS**

Catalog number	Cord length	Plug configuration
09723	3 ft	
09724	4 ft	Right angle
09726	6 ft	
09733	3 ft	
09734	4 ft	Straight
09736	6 ft	

The information presented here is, to the best of our knowledge, true and accurate. However, since conditions of use are beyond our control, all recommendations or suggestions are presented without guarantee or responsibility on our part. We disclaim all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Coleman Cable Inc. Any information contained herein shall not be disclosed to any party without written consent of Coleman Cable Inc.

Coleman Cable Inc. 1530 Shields Drive, Waukegan, IL 60085 800.323.9355 www.colemancable.com