



## PRODUCT SPECIFICATION

**CATALOG NUMBER:** See table below  
**DESCRIPTION:** Automotive battery booster cables with Polar-Glo clamps  
**APPROVALS:** UL Listed

### CONSTRUCTION PARAMETERS:

Cable length: See table below  
 Conductor: See table below  
 Insulation material: TPE  
 Cable insulation color: Red (4 gauge), orange (6 gauge)  
 Cable legend type: Indent print  
 Clamp material: PVC coated steel  
 Contact jaw material: Copper plated steel  
 Polarity indication: Red and black clamps, "+POS" and "-NEG" stamped into clamp handles, phosphorescent labels on clamp handles

### ELECTRICAL PROPERTIES:

Cable temperature rating: -40 to +60 °C  
 Maximum operating current: See table below



Catalog number	Cable gauge	Cable length	Conductor stranding	Current rating
08565	6 ga Cu	12 ft	77 / 0.0212	300 A
08566	equivalent	16 ft	CCA	250 A
08665	4 ga Cu equivalent	12 ft	126 / 0.0212 CCA	400 A
08666		16 ft		350 A
08660		20 ft		300 A
08662		25 ft		250 A

The information presented here is, to the best of our knowledge, true and accurate. However, since conditions of use are beyond our control, all recommendations or suggestions are presented without guarantee or responsibility on our part. We disclaim all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Coleman Cable Inc. Any information contained herein shall not be disclosed to any party without written consent of Coleman Cable Inc.