

•••••••••••••••••••••••••••••••••••••••	See table below 6/3 & 8/1 SEW, 125/250V 50A RV power supply cords	
APPROVALS: UL	UL/CUL Listed RV power supply cords	
CONSTRUCTION PARAMETERS:		
Conductors:		(3) 6 AWG (7x38/30) bare copper and
		(1) 8 AWG (7x24/30) bare copper
Conductor O.D. (nom):		0.185" (6 ga), 0.153" (8 ga)
Insulation material:		
Insulation O.D. (nom)		0.326" (6 ga), 0.277" (8 ga)
Conductor color code: Jacket material:		Black White Red (6 ga), Green (8 ga) TPE
Overall cable O.D. (nom):		1.049"
Temperature rating:		-50 to +90 deg C
Black White Green 00- Red		
Note: Plug style may vary		
Plug configuration:		NEMA 14-50P
Electrical ratings:		125/250 VAC 50A
Plug material:		PVC
Removal of jacket (nom):		7" None
Conductor strip: None		
CATALOG NUMBERS:		
Le	ngth	Catalog number
2	25 ft	09560*
	28 ft	09564*
	0 ft	09562
3	6 ft	09561
* - UL listed for OEM sale		* - UL listed for OEM sale

The information presented here is, to the best of our knowledge, true and accurate. However, since conditions of use are beyond our control, all recommendations or suggestions are presented without guarantee or responsibility on our part. We disclaim all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Coleman Cable Inc. Any information contained herein shall not be disclosed to any party without the written consent of Coleman Cable Inc.

Coleman Cable Inc. 1530 Shields Drive, Waukegan, IL 60085 800.323.9355 www.colemancable.com