



PRODUCT DATA SHEET

Controlled Document - Engineering Drive

1530 Shields Drive
Waukegan, IL 60085
Toll-Free (800) 323-9355
Fax: (847) 689-1192

PART NUMBER: 51544
DESCRIPTION: 14/4 Flat Trailer Cable
CONSTRUCTION: This cable consists of four bare copper conductors with PVC insulation laid flat and parallel and bonded together.
SPECIFICATIONS: SAE J1128
APPLICATION: Trailer Light Hookup Wire

Construction Parameters:

Conductor	14 Gauge Bare Copper
Stranding	19/27
Insulation Material	PVC
Insulation Thickness	0.023" Nom.
Insulated Conductor Diameter	0.120" x 0.480" Nom.
Approximate Cable Weight	#N/A

Electrical Properties:

Temperature Rating	-20°C to 60°C
Operating Voltage	300 V RMS Max.
DC Resistance per Conductor @ 20°C	#N/A

Insulation/Jacket Color	White Brown Yellow Green
-------------------------	--------------------------

Legend	None
--------	------

This product complies with European Directive 2002/95/EC (RoHS)

On special orders, the customer will accept all factory lengths and +/- 10 percent of total order requested.

The information presented here is, to the best of our knowledge, is true and accurate. However, since conditions of use are beyond our control, all recommendations or suggestions are presented without guarantee or responsibility on our part. We disclaim all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Coleman Cable. Any information contained herein shall not be disclosed to any party without written consent of Coleman Cable.

Customer Name _____

Customer Approval _____

Specification Issue Date: March 12, 2008