



PRODUCT SPECIFICATION

CATALOG NUMBER: 01980

PRODUCT DESCRIPTION: Mini portable power distribution box

NRTL APPROVAL: c(ETL)us Listed to UL 1640 and CAN/CSA C22.2 No. 14

PRODUCT DESCRIPTION

Power inlet: NEMA L14-30P 30A 125/250V
twist-to-lock flanged inlet

Power outlets: (4) NEMA 5-20R 20A 125V duplex
straight blade receptacles

Over-current protection: (1) 20A circuit breaker for each pair
of duplex receptacles





Ground fault protection: (1) Class A GFCI for each pair
of duplex receptacles

Over-voltage protection: Provided by GFCI

Open-neutral protection: Provided by GFCI

Input rating: 30A 125/250V 3-pole 4-wire grounding

Output rating: 40A 125V 2-pole 3-wire grounding (20A max per circuit)



Enclosure type: NEMA Type 1

Enclosure material: Carbon steel, with yellow exterior paint finish

External dimensions (approx): 10" x 7-1/8" x 11" high

Weight (approx): 9 lbs.

The information presented here is, to the best of our knowledge, true and accurate. However, since conditions of use are beyond our control, all recommendations or suggestions are presented without guarantee or responsibility on our part. We disclaim all liability in connection with the use of information contained herein or otherwise.

This specification is the proprietary intellectual property of Coleman Cable Inc.. Any information contained herein shall not be disclosed to any party without the written consent of Coleman Cable Inc..