Multipin Design Thermocouple Connectors
Model MTC with 200°C (392°F)


Maximum Service Temperature

MTC Series

For Five-Cavity Female Flanged Connector-**Pins Sold Separately**

- ✓ Thermocouple Alloy Pins
- ✓ Air and Moisture **Resistant Connection**
- Removable Crimp Contacts
- **∠** 20 to 24 AWG Stranded Wire
- **✓** Aluminum Shells
- ✓ Black Anodized Finish
- ✓ Threaded Coupling

Recommended for Use With Stranded Wire



cavity sequence. The first and last

cavities are numbered and every tenth cavity is bracketed.



Although MTC PINS do not carry a MIL. SPEC. NUMBER, they do meet the performance requirements of MIL-C-26500E and are intermateable with MIL-C-26500 connectors.

Shown actual size.

Visit newportUS.com for multipair extension cable.

Shown with In-Line Cable Connector with Optional Backshell Cable Clamp

NEWPORT® sturdy multipin connectors provide an efficient means of joining multiwire thermocouple cables. They can be used with multiple extension wire for rapid, convenient connections and for dismantling an apparatus without handling individual sensors.

When used with MTC Series pins, the connector design utilizes a combination of resilient and rigid dielectric insulators to eliminate internal air voids and prevent the passage of air and moisture into or through the connector. Connectors can withstand ambient temperatures to 200°C (392°F), contributing to an extended connector life.



Multipin Connector Bodies*

To Order Visit newportUS.com/mtc for Pricing and Details				
Number of Cavities	MC Male Cord	FC Female Cord	FF Female Flanged	Backshell Cable Clamp**
5	MTC-5-MC	MTC-5-FC	MTC-5-FF	MTC-5-SHL
12	MTC-12-MC	MTC-12-FC	MTC-12-FF	MTC-12-SHL
24	MTC-24-MC	MTC-24-FC	MTC-24-FF	MTC-24-SHL
41	MTC-41-MC	MTC-41-FC	MTC-41-FF	MTC-41-SHL
55	MTC-55-MC	MTC-55-FC	MTC-55-FF	MTC-55-SHL

* Contacts not included. Order from next page.

** Backshell cable clamps provide effective support for the cable at the male or female connector and prevent twisting and pulling.

Ordering Examples: MTC-55-FC, multipin connector body. MTC-24-FF, female

flanged connector.