

Ultimate Connector with Integral Cable Clamp Cap

Glass Filled Nylon Range -29 to 220°C (-20 to 425°F)
Type OSTW Standard Size with Cable Clamp Cap

OSTW-CC Series



- ✓ Integral Cap and Cable Clamp
- ✓ Strain Relief With Grommet
- ✓ Pull Test High Rating
- ✓ Captive Cover and Clamp Screws
- ✓ Wire Termination Up to Size 14 AWG
- ✓ 1/8" Back Plate (Supplied) Accepts: Stranded, Solid, TWSH, Overbraid, or RSC Coil Cord Wire
- ✓ 1/4" Back Plate (Optional) Clamps to 8.2 mm (0.325") OD
- ✓ Contact Washers for Quick Connect Wire Terminations—No Wire Loop Required
- ✓ Internal Wire Divider
- ✓ Write-On Window
- ✓ Combination Phillips/Slot Screws
- ✓ 100% Top Side Assembly

**Incredible Labor Saver!
No Loose Screws, All
Cover Screws Are
Captive!**

Back plate: 1/8" ϕ supplied to fit soft and overbraid wire. Optional: 1/4" ϕ to fit armored cable.

Terminate straight wire, wire loop not necessary.

See newportUS.com for TC wire selection.

Grommets included.

Contact washers.

All screws are combination head.

Hollow pin standard, solid pin available.

OSTW-CC-K-M shown actual size.

OSTW-CC-K-F shown actual size.

SMPW-CC-K-M shown actual size.

**Universal Female
Mates with Standard or
Miniature Thermocouple
Connectors**

**Reduce Assembly
Time From 3 Minutes
to Less Than
1 Minute!**



