



2.0mm Wire to Board Header Straight (R/A) Type

MATERIAL

Insulator : Polyester
Contact Pin : Brass




SPECIFICATION

Current Rate : 2 AMP
Insulation Resistance : 100MΩ MIN.
Contact Resistance : 20mΩMax.
Operation Temperature : -25°C to +85°C






Detail Dimensions



725-71-xxTW01



725-72-xxTW01



Recommended P.C.B Layout



Order Information

725-7 x - xx T W xx
1 2 3 4 5

1. 1: Straight Type
2: Right Angle Type
2. No. of contacts
3. T: Tin Plating
4. W: White Insulator
5. Pinrex internal code

Standard Parts	Type
725-71-xxTW01	Straight
725-72-xxTW01	Right Angle

Number Of Contacts

Unit: mm

Poles	DIM A	DIM B	Poles	DIM A	DIM B	Poles	DIM A	DIM B						
4	2.00	6.00	18	16.00	20.00	32	30.00	34.00						
6	4.00	8.00	20	18.00	22.00	34	32.00	36.00						
8	6.00	10.00	22	20.00	24.00	36	34.00	38.00						
10	8.00	12.00	24	22.00	26.00	38	36.00	40.00						
12	10.00	14.00	26	24.00	28.00	40	38.00	42.00						
14	12.00	16.00	28	26.00	30.00									
16	14.00	18.00	30	28.00	32.00									