





ALL NEW PRODUCTS!



# Heyco® SunClamp™ Stainless Steel Cable Clamps

MOUNTING HOLE DIAMETER		SCREW SIZE	PART DIMENSION A		PART NO.	DESCRIPTION
in.	mm.		in.	mm.		
<b>Standard</b>						
.203	5,2	10	.250	6,3	<b>S3374</b>	CC H 1/4 SS
			.375	9,5	<b>S3376</b>	CC H 3/8 SS
			.500	12,7	<b>S3378</b>	CC H 1/2 SS
			.625	15,9	<b>S3380</b>	CC H 5/8 SS
			.750	19,1	<b>S3382</b>	CC H 3/4 SS
			.875	22,2	<b>S3384</b>	CC H 7/8 SS
<b>LDPE Coated</b>						
.203	5,2	10	.250	6,3	<b>S3324</b>	CC H 1/4 SSC
			.375	9,5	<b>S3326</b>	CC H 3/8 SSC
			.500	12,7	<b>S3328</b>	CC H 1/2 SSC
			.625	15,9	<b>S3330</b>	CC H 5/8 SSC
			.750	19,1	<b>S3332</b>	CC H 3/4 SSC
			.875	22,2	<b>S3334</b>	CC H 7/8 SSC

- For clamping cable or tubing securely into place, especially in **harsh environments**.
- Smooth "coined" clamp edges prevent damage to cable insulation.
- Constructed from corrosion resistant 304 stainless steel.
- Insulated parts are constructed from 304 stainless steel and coated with polyolefin, a thermoplastic co-polymer that provides a durable non-toxic, odorless coating that has very good low temperature flexibility and excellent electrical properties. This coating also has FDA food contact approval.
- Consult Heyco for larger sizes.
- Not for use in a marine salt water environment. Contact Heyco for alternative materials.



# Heyco® SunStars™ Grounding Spacers for Module to Rack Applications

PART DIMENSIONS				PART NO.	DESCRIPTION
Inside Dia.		Outside Dia.			
in.	mm.	in.	mm.		
.312	7,9	.75	19,1	<b>S6480</b>	SSGS 750-312
		1.00	25,4	<b>S6481</b>	SSGS 1000-312
		1.25	31,8	<b>S6482</b>	SSGS 1250-312

- Creates bond between PV module and racking system.
- UL Recognized to UL Standard 2703
- Universal design for quick installation. Extrusions are symmetrically opposed for maximum strength.
- Stainless steel construction for maximum durability.

**Material**                      304 Stainless Steel

Quick Specs