



Heyco® -Tite Aluminum Liquid Tight Cordgrips

ALL NEW PRODUCTS!




Straight-Thru, NPT Hubs

The Ultimate in Liquid Tight Strain Relief Protection

- **Aluminum construction** provides excellent durability and performance for most **industrial applications**.
- For use in both indoor and outdoor applications to prevent cable pull-out, control arc of bend, and to provide a tight seal against environmental elements such as dirt, moisture, and coolants.
- IP 67 rated.
- Approved for NEMA 6 applications.
- Protect cable from damage and pull-out and are used in conduit hubs or knock-outs at the point where the electrical cable is to be terminated.
- Unique design with a combination tightening surface that includes both a hex area and a knurled surface.
- Anti-friction washer allows for easier compression.

CABLE DIA. RANGE				PART NO.	THREAD SIZE	UL	PART DIMENSIONS							
Minimum		Maximum					Machined Aluminum	A Clearance Hole Dia.		B Max. O.A. Length		C Thread Length		D Wrenching Flat Size
in.	mm.	in.	mm.		in.	mm.		in.	mm.	in.	mm.	in.	mm.	
.562	14,3	.688	17,5	M5062	NPT 1-1/4	UL	1.72	43,7	2.50	63,5	.69	17,5	2.25	57,2
.688	17,5	.812	20,6	M5063										
.750	19,1	.875	22,2	M5064										
.875	22,2	1.000	25,4	M5065										
1.000	25,4	1.125	28,6	M5066										
1.125	28,6	1.250	31,8	M5067										
1.250	31,8	1.375	34,9	M5068	NPT 1-1/2	UL	1.97	50,0	2.50	63,5	.69	17,5	2.25	57,2
.562	14,3	.688	17,5	M5069*										
.688	17,5	.812	20,6	M5070										
.750	19,1	.875	22,2	M5071										
.875	22,2	1.000	25,4	M5072										
1.000	25,4	1.125	28,6	M5073										
1.125	28,6	1.250	31,8	M5074	NPT 2	UL	2.46	62,5	3.12	79,2	.80	20,3	2.83	71,9
1.250	31,8	1.375	34,9	M5075										
1.250	31,8	1.375	34,9	M5080										
1.312	33,3	1.437	36,5	M5081										
1.438	36,5	1.562	39,7	M5082										
1.562	39,7	1.688	42,9	M5083										
1.688	42,9	1.812	46,0	M5084										

Assembled O-ring **INCLUDED**. *Not UL Listed or CSA Certified.
Locknut not included - See page 3-40 for Metal Locknuts.



SUGGESTED CLEARANCE HOLE FOR NON-THREADED MOUNTING

Quick Specs

Material Certifications

Flammability Rating
Temperature Rating
IP Rating

Aluminum with Neoprene Sealing Gland and Viton® O-Ring
 UL Listed under Underwriters' Laboratories File E51579
 SR Certified by Canadian Standard Association File 258093
 Approved for NEMA 6 Applications

94V-2
 -40°F (-40°C) to 250°F (121°C)
 IP 67