



# Heyco® -Tite Cast Aluminum Liquid Tight Cordgrips

**ALL NEW PRODUCTS!**






## Straight-Thru, NPT Hubs

*The Ultimate in Liquid Tight Strain Relief Protection*

CABLE DIA. RANGE				PART NO. Cast Aluminum	THREAD SIZE	UL	PART DIMENSIONS								
Minimum		Maximum					A		B		C		D		
in.	mm.	in.	mm.				Clearance Hole Dia.	in.	mm.	Max. O.A. Length	in.	mm.	Thread Length	in.	mm.
1.688	42,9	1.812	46,0	<b>M5091</b>	NPT 2-1/2	UL	2.96	75,2	4.20	106,7	1.28	32,5	4.00	101,6	
1.812	46,0	1.938	49,2	<b>M5092</b>											
1.938	49,2	2.062	52,4	<b>M5093</b>											
2.062	52,4	2.188	55,6	<b>M5094</b>											
2.188	55,6	2.312	58,7	<b>M5095</b>											
2.312	58,7	2.438	61,9	<b>M5096</b>											
1.688	42,9	1.812	46,0	<b>M5097</b>	NPT 3	UL	3.58	90,9	4.20	106,7	1.31	33,3	4.00	101,6	
1.812	46,0	1.938	49,2	<b>M5098</b>											
1.938	49,2	2.062	52,4	<b>M5099</b>											
2.062	52,4	2.188	55,6	<b>M5100</b>											
2.188	55,6	2.312	58,7	<b>M5101</b>											
2.312	58,7	2.438	61,9	<b>M5102</b>											
2.437	61,9	2.625	66,7	<b>M5103</b>	NPT 3	*	3.50	88,9	4.85	123,2	1.39	35,3	4.75	120,7	
2.625	66,7	2.812	71,4	<b>M5104</b>											
2.812	71,4	3.000	76,2	<b>M5105</b>											
3.000	76,2	3.250	82,6	<b>M5106</b>											

- **Aluminum construction** provides excellent durability and performance for most **industrial applications**.
- For use in both indoor and outdoor applications to prevent cable pull-out, control arc of bend, and to provide a tight seal against environmental elements such as dirt, moisture, and coolants.
- IP 67 rated.
- Approved for NEMA 6 applications.
- Protect cable from damage and pull-out and are used in conduit hubs or knock-outs at the point where the electrical cable is to be terminated.
- Unique design with a combination tightening surface that includes both a hex area and a knurled surface.
- Anti-friction washer allows for easier compression.

Assembled O-ring **INCLUDED**. \*Not UL Listed or CSA Certified.  
Locknut not included - See page 3-40 for Metal Locknuts.



SUGGESTED CLEARANCE HOLE FOR NON-THREADED MOUNTING

**Material Certifications**

- Aluminum with Neoprene Sealing Gland and Viton® O-Ring
- UL Listed under Underwriters' Laboratories File E51579
- CSA Certified by Canadian Standard Association File 258093
- Approved for NEMA 6 Applications

Flammability Rating  
Temperature Rating  
IP Rating

94V-2  
-40°F (-40°C) to 250°F (121°C)  
IP 67

*Quick Specs*