



- HEYCaps can be used as either caps or plugs.
- Because they are tapered in design and made from highly flexible polyethylene, they not only fit snugly but are readily removable.
- Especially recommended for use on threaded external NPT Fitting hubs.
- Part dimensions are based on average threaded hub fit. Before ordering in quantity, please sample HEYCaps.
- Recommended Closures:
   Threaded hubs where Cap dimension
   "B" is at least 1% smaller than the hub to be capped. Minimum .020" (0,5 mm).
- Typical Applications:
  - -Threaded external NPT fittings
  - -Tube and hydraulic fittings
  - -Unthreaded standard weight pipe

## **HEYCap<sup>™</sup> Tapered Caps\***





For NPT Fitting Hubs

Fits this	PART	DESCRIPTION	PART DIMENSIONS							
NPT HUB	NO.		Body Diameters**				Head Di	iameter	Depth	
or Mounting	Red		A - Major		B - Minor		C		D	
Hole			in.	mm.	in.	mm.	in.	mm.	in.	mm.
1/8	G5014	TCP 49-42 <sup>†</sup>	.42	10,7	.36	9,0	.63	16,0	.38	9,7
1/4	G5020	TCP 61-55	.55	13,8	.47	11,9	.75	19,1	.44	11,2
3/8	G5027	TCP 76-69	.69	17,6	.61	15,6	.88	22,4	.50	12,7
1/2	G5035	TCP 91-85	.85	21,6	.74	18,8	1.06	26,9	.63	16,0
3/4	G5047	TCP 115-108	1.08	27,5	.93	23,7	1.31	33,3	.75	19,1
1	G5057	TCP 136-130	1.30	33,0	1.17	29,8	1.50	38,1	.81	20,6
1-1/4	G5071	TCP 168-162	1.62	41,1	1.50	38,0	1.88	47,8	.75	19,1
1-1/2	G5080	TCP 195-189	1.89	48,0	1.72	43,6	2.13	54,1		
2	G5096	TCP 246-240	2.40	61,0	2.24	56,8	2.63	66,8	1.00	25,4
2-1/2	G5110	TCP 299-295	2.95	74,9	2.69	68,2	3.13	79,5		
3	G5116	TCP 356-349	3.49	88,7	3.20	81,3	3.69	93,7	1.13	28,7

<sup>\*</sup>May also be used as Plugs: to determine Outside Diameters, add approximately .06'' (1,5 mm) to Inside Diameter dimensions.









Material Low Density Polyethylene

Standard Color: Red

Applicable Specs: MIL-C-5501/7 (MIL-C-52078), NAS-835

<sup>\*\*</sup>Body Diameters reference Inside dimensions.

<sup>†</sup>Part No. G5014 functions as a cap for NPT 1/8 Hubs and a Plug for NPT 1/4 Hubs. Standard color red.