



- Small, snap-in nylon receptacles for low cost, insulated, quick connection or disconnection of your wires, through panels, housings or detachable shrouds.
- Typical uses are data processing and vending machines, motors, power supplies, and controls.
- Non-polarized HEYConnects feature 1/4" (6,4 mm) internal brass male terminals, to mate with standard 1/4" (6,4mm) female Quick-Connects.
- Polarized HEYConnects feature 1/4" (6,4 mm) and 3/16" (4,7 mm) internal brass male terminals, to mate with standard 1/4" and 3/16" female Quick-Connects.
- Two-terminal HEYConnect bodies feature markings that correlate the terminals, front to back.
- Available in double-male and male-solder configurations.
- Consult Heyco for white and other colors.

## HEYConnect™ Terminal Bushings

### Bushings with Double Male Terminals

TERMINALS		PANEL DIMENSIONS						PART NO.	DESCRIPTION	PART DIM. D	
No. of Poles	Width in.   mm.	A Mounting Hole Diameter in.   mm.		B To Prevent Rotation in.   mm.		C Maximum Panel Thickness in.   mm.				Black	Overall Length in.   mm.
<b>Non-polarized</b>											
1	.25   6,4	.500	12,7	.47	11,8	.13	3,2	<b>4240</b>	DC 50-1-M/M	.94	23,9
1	.25   6,4	.687	17,4	.64	16,3	.13	3,2	<b>4380</b>	DC 50-1-M/M Tinned		
2	.25   6,4	.687	17,4	.64	16,3	.13	3,2	<b>4440</b>	DC 68-1-M/M	.94	23,9
2	.25   6,4	.687	17,4	.64	16,3	.13	3,2	<b>4440</b>	DC 68-2-M/M		
<b>Polarized</b>											
1	.19   4,8	.687	17,4	.64	16,3	.13	3,2	<b>4428</b>	DC 68-2-M/M Polarized	.94	23,9
1	.25   6,4										

Standard color black.

### Bushings with Tinned Male to Solder Terminals

TERMINALS		PANEL DIMENSIONS						PART NO.	DESCRIPTION	PART DIM. D	
No. of Poles	Width in.   mm.	A Mounting Hole Diameter in.   mm.		B To Prevent Rotation in.   mm.		C Maximum Panel Thickness in.   mm.				Black	Overall Length in.   mm.
<b>Non-polarized</b>											
1	.25   6,4	.500	12,7	.47	11,8	.13	3,2	<b>4270</b>	DC 50-1-M/S-Tinned	.92	23,4
1	.25   6,4	.687	17,4	.64	16,3	.13	3,2	<b>4410</b>	DC 68-1-M/S-Tinned		
2	.25   6,4	.687	17,4	.64	16,3	.13	3,2	<b>4470</b>	DC 68-2-M/S-Tinned	.92	23,4
2	.25   6,4	.687	17,4	.64	16,3	.13	3,2	<b>4470</b>	DC 68-2-M/S-Tinned		
<b>Polarized</b>											
1	.19   4,8	.687	17,4	.64	16,3	.13	3,2	<b>4468</b>	DC 68-2-M/S-Pol Tinned	.92	23,4
1	.25   6,4										

Standard color black.

Quick  
Specs



# HEYConnect™ Terminal Bushings

