




- Close unneeded sheet metal panel holes, ergonomically.
- Flush button head style.
- Quick, easy installation; quick, easy removal, too.
- Heyco Metric Ergonomic Plugs offer greater versatility because their pliable nature allows one plug size to fit a variety of different sized holes.
- Available in multiple sizes from .57" (14,5 mm) through 1.34" (34,0 mm) diameter holes.
- Molded from thermoplastic rubber.


Heyco[®] Metric Ergonomic Plugs

For Panel Thickness from 0,8 mm (.03") to 2,0 mm (.08") Mounting Hole Diameter Range: 14,5 mm (.57") to 34,0 mm (1.34")

MOUNTI	NG HOLE DIAMETER PART NO. DESCRIPTION PART DIMENSIONS									
NOMINAL	DIAMETE	R RANGE			P	١	E	3	(;
			Black		Head Di	ameter	Bottom D	Diameter	Overall	Height
mm.	mm.	in.			mm.	in.	mm.	in.	mm.	in.
15	14,5 - 16,0	.5763	9690	SMP E-M15	25,0	.98	18,0	.71	7,8	.31
17	15,2 - 18,0	.6571	9691	SMP E-M17	28,0	1.10	20,3	.80	1,0	.31
19	18,5 - 20,0	.7379	9692	SMP E-M19	30,2	1.19	22,5	.89	7,8	.31
21	20,5 - 22,0	.8187	9693	SMP E-M21	32,0	1.26	24,3	.96	7,0	.01
23	22,5 - 24,0	.8795	9694	SMP E-M23	34,0	1.34	26,4	1.04	7,8	.31
25	24,5 - 26,0	.97 -1.02	9695	SMP E-M25	35,0	1.38	28,0	1.10	7,0	.01
27	26,5 - 28,0	1.04 -1.10	9696	SMP E-M27	38,0	1.50	30,3	1.19	7,8	.31
29	28,5 - 30,0	1.12 -1.18	9697	SMP E-M29	40,0	1.58	32,3	1.27	7,0	.01
31	30,5 - 32,0	1.20 -1.26	9698	SMP E-M31	42,0	1.65	34,3	1.35	7 Q	.31
33	32,5 - 34,0	1.28 -1.34	9699	SMP E-M33	44,0	1.73	36,3	1.43	7,8	.31

Standard color black.







Heyco® Insulation Plug

No Maximum Panel Thickness

MOUNTING		PART NO.		DESCRIPTION	PART DIMENSIONS			
HOLE Diameter		Black White			A Head Diameter		в Overall Height	
in.	mm.				in.	mm.	in.	mm.
1.000	25,4	3149	3150	IPW 1	1.234	31,3	.687	17,5

Standard color black. Consult Heyco for other colors.





Material	SMP E Flex Temp (Thermoplastic Rubber)
Material	IPW Nylon 6/6
Flammability Rating	94V-2
Temperature Rating	(Both) -40°F (-40°C) to 221°F (105°C)
romporataro riating	(35) 10 1 (10 5) 15 221 1 (105 5)



- Closes cavity-fill insulation holes in wood and other type siding.
- Fills holes in surfaces of unspecified thickness including cabinetry, furniture, display cases even masonry.
- Convex, matte finish head blends with various surfaces.
- Quick and easy installation with fingertip pressure (no tool required).
- Holds securely in hole.
- Molded of type 6/6 Nylon.
 Flammability classification 94V-2.

