



- Provide a positive seal on NPS threaded ports.
- Flange compresses against the mounting hole surface area, keeping contaminants from the spot face.
- Round, 12-point socket pattern Head.
- Integral, serrated Shoulder Washer.
- Applicable Specs: MIL-C-52078, MIL-C-5501/5, NAS 840.


Heyco® Threaded Plugs for Straight Threaded Ports

For NPS Threaded Ports

12 Point Socket Head

	PART NO.	. DESCRIPTION PART DIMENSIONS							
NPS THREADED PORT SIZE	Red		A 12-Point Socket Size	B Depth		C Head Height		D Shoulder Diameter	
				in.	mm.	in.	mm.	in.	mm.
1/8	G5410	PNPS 1/8	9/16	.27	6,9	.31	7,9	.56	14,2
1/4	G5411	PNPS 1/4	9/16	.37	9,4	.31	7,9	.74	18,8
3/8	G5412	PNPS 3/8	9/16	.33	8,4	.38	9,7	.83	21,1
1/2	G5413	PNPS 1/2	9/16	.55	14,0	.37	9,4	1.04	26,4
3/4	G5414	PNPS 3/4	9/16	.63	16,0	.41	10,4	1.31	33,3

Standard color red.





Maximum Temperature Rating

HDPE 215°F (102°C)