HEYCO



- Ideal for securing, insulating, and routing cable and tubing.
- Cable and wire can be installed or removed for repair without removing clamp.
- Mounts with screws, mounting buttons or rivets.



- Retainer clip allows clamp to be pre-positioned on hose before final installation.
- Double row of teeth for more secure grip.
- Quick and easy installation.
 Tighten instantly with hand pliers or Air Tool (below).
- Reusable. Can be removed without cutting.
- Supertough nylon clamps offer additional clamping strength.
- Outlast tubing under pressure.
- Non-conductive and non-magnetic.
- No moving pieces to seize or vibrate loose.
- Maximum Pressure Rating: 200 PSI.




Heyco® Wire Harness Clamps




	MOUNTING Hole Diameter		SCREW SIZE	A Bundle Dia.		PART DIMENSION B Overall Length		C		PART NO. Natural	DESCRIPTION	STYLE
	in.	mm.		in.	mm.	in.	mm.	in.	mm.			
Snap Mouth *												
	.157	4,0	#8	.71	18,0	1.38	35,1	.50	12,7	4148	WHCX 750	1
	Open Mouth											
	.157	4,0	#8	.13	3,2	.77	19,5	.34	8,5	4149	WHC 125	2
				.25	6,4	.86	21,8	.41	10,4	4150	WHC 250	
				.38	9,0	.83	21,0	.40	10,2	4151	WHC 375	
				.50	12,5	1.16	29,4	.40	10,2	4152	WHC 500	
	.205	5,2	#10	.63	15,9	1.13	28,6	.50	12,7	4153	WHC 625	3
				.75	19,1	1.28	32,5	.50	12,7	4154	WHC 750	
				1.00	25,4	1.53	38,9	.50	12,7	4210	WHC 1000	
				1.50	38,1	2.12	53,9	.50	12,7	4211	WHC 1500	


Standard color natural.

^{*}Bundle Diameter in closed position.











Heyco® Nylon Lockit™ Hose Clamps

Minii Diam in.	mum	LAMP RANGE Maximum Diameter in. mm.		PART NO. Black	DESCRIPTION	PART DIMI A Clamp Thickness in. mm.		ENSIONS B Strap Thickness in. mm.	
	8,7 13,5 17,0	.41 .59 .81	10,3 15,1 20,6	2388 2391 2393	LHC 344 LHC 531 LHC 672	.25	6,4	.08	2,0

Standard color black.





Material Flammability Rating Temperature Range WHCX & WHC Nylon 6/6 94V-2 32°F (0°C) to 185°F (85°C) **LHC**Nylon 6/6 Supertough
94HB
32°F (0°C) to 185°F (85°C)