



Regular Nytyes

- Smooth, radiused edges ensure that Nytyes won't cut into the cable's insulation—or the installer's hand.
- One-piece design reduces cost and installation time.
- Nytyes feature a bent tip for ease of pickup and insertion around small bundles. V-shaped raised ridges on the tip provide a sure grip.
- Close, evenly spaced teeth permit fine adjustment—from .025" (0,6 mm) on the smallest Nytyes to .063" (1,6 mm) on the largest.

Screw Mountable Nytyes

- Molded-in screw hole mount provides one-piece mounting and bundling.
- Mounting screws not included.

Push Mountable Nytyes


- Snap quickly into holes with only fingertip pressure.
- Provide one-piece mounting and bundling.
- Hold securely in panels up to 1/8" (3,2 mm) thick.





Heyco® Nytye® Nylon Cable Ties

PART SPECIFICATIONS				PART NO.		DESCRIPTION	PART DIMENSIONS						
Max. Tensile Strength	Max. Bundle Diameter	Natural	UV Black	A Length	B Width		C Thickness	Min Bundle Diameter	in.	mm.	in.	mm.	
lbs.	N	in.	mm.										
Regular Nytyes®													
18	80	.75	19,1	3500	3502	NT 70	3.80	97					
		1.50	38,1	3503	3504	NT 70L	6.25	159	.09	2,3	.05	1,1	
		2.00	50,8	3506	3507	NT 70E	8.00	203					
30	133	1.00	25,4	3510	3511	NT 90	5.20	132	.12	2,9			
		1.25	31,8	3515	3516	NT 120	5.67	144	.14	3,4	.06	1,4	.06
		2.00	50,8	3850	3851	NT 170	8.25	210			.05	1,3	1,6
		1.75	44,4	3520	3521	NT 150	7.50	191					
		3.00	76,2	3525	3526	NT 250	11.25	286	.19	4,8	.06	1,4	
		4.00	101,6	3530	3531	NT 330	14.50	368					
Screw Mountable Nytyes®													
30	133	1.00	25,4	3550	-	MNT 90	5.50	140	.12	2,9	.05	1,1	Screw #
		1.25	31,8	3555	-	MNT 120	6.50	165	.14	3,4	.05	1,3	4
		1.75	44,4	3560	-	MNT 150	8.00	203	.19	4,8	.06	1,4	8
													10
Push Mountable Nytyes®													
40	180	1.42	36,0	-	3907	PWMS-155 HSB	6.23	158	.14	3,5	.05	1,2	Mounting Hole Dia.
		1.75	44,4	3904	-	PMT 150	8.00	203	.19	4,8	.06	1,4	.19
													6,4


Standard color natural. UV Black at extra charge. Consult Heyco for Nytyes in colors.




Regular Nytyes



Screw Mountable Nytyes



Push Mountable Nytyes



Quick Specs

Material	Nylon 6/6
Certifications	Recognized under the Component Program of Underwriters' Laboratories File E54523
Flammability Rating	94V-2
Temperature Range	32°F (0°C) to 185°F (85°C)