




- Slit design allows side entry and encirclement of preassembled harnesses and capillary tubes.
- Unique slit design allows for wire breakouts.
- Heyco-Flex V is lightweight and flexible, yet durable enough to meet your wire management requirements.
- Multiple sizes 1/8" to 1-1/2".
- All nylon construction resists salt water, weak acids, gasoline, alcohol, oil, grease, and common solvents.
- Quick installation; cuts with utility knife, PVC cutter or Heyco cutting tool #8340. See page 2-2 in Heyco Catalog 114.

Heyco-Flex™ V Nylon Slit Tubing

NOMINAL DIAMETER	PART NO.	DESCRIPTION	PART DIMENSIONS						ROLL LENGTH
			A Outside Diameter		B Inside Diameter		Wall Thickness Range		
in.	Black		in.	mm.	in.	mm.	in.	mm.	ft.
1/8	1634A	HF5 1/8	.26	6,6	.17	4,3	.01-.02	0,2-0,5	100
1/4	1635A	HF5 1/4	.39	9,9	.29	7,3			
11/32	1636A	HF5 11/32	.51	13,0	.35	8,8			
3/8	1637A	HF5 3/8	.53	13,5	.42	10,5			
7/16	1638A	HF5 7/16	.63	15,9	.44	11,2			
1/2	1639A	HF5 1/2	.64	16,2	.53	13,3			
5/8	1641A	HF5 5/8	.81	20,5	.66	16,8			
3/4	1642A	HF5 3/4	.93	23,6	.79	20,1			
1	1643A	HF5 1	1.12	28,5	.92	23,3			
1-1/16	1644A	HF5 1-1/16	1.22	30,9	1.01	25,6			
1-1/4	1646A	HF5 1-1/4	1.49	37,9	1.28	32,6			
1-1/2	1649A	HF5 1-1/2	1.73	43,9	1.47	37,2			

Standard color black.



Quick Specs

Material	Polyamide 6 Nylon
Flammability Rating	94HB
Temperature Range	-40°F (-40°C) to 239°F (115°C) Continuous -40°F (-40°C) to 374°F (190°C) Intermittent