


## Heyco® Polyurethane Adhesive-Back Bumpers


PART DIMENSIONS				PART NO.		DESCRIPTION	Pieces per Pad
A Diameter		B Height		Clear	Black		
in.	mm.	in.	mm.				
<b>HSA Series</b> Hemi							
.25	6,4	.06	1,6	<b>N040</b>	<b>N140</b>	HBA 250-06	578
.31	7,9	.09	2,3	<b>N027</b>	<b>N127</b>	HBA 312-09	450
.34	8,6	.09	2,3	<b>N007</b>	<b>N107</b>	HBA 335-09	
.38	9,7	.15	3,8	<b>N012</b>	<b>N112</b>	HBA 375-15	200
.44	11,2	.20	5,1	<b>N002</b>	<b>N102</b>	HBA 440-20	242
.62	15,7	.31	7,9	<b>N015</b>	<b>N115</b>	HBA 620-31	128
.70	17,8	.38	9,7	<b>N008</b>	<b>N108</b>	HBA 700-38	98
<b>CBA Series</b> Cylinder							
.38	9,7	.19	4,8	<b>N035</b>	<b>N135</b>	CBA 370-19	200
.50	12,7	.06	1,5	<b>N005</b>	<b>N105</b>	CBA 500-06	200
		.14	3,6	<b>N001</b>	<b>N101</b>	CBA 500-14	
.65	16,5	.25	6,4	<b>N006</b>	<b>N106</b>	CBA 500-25	128
		.40	10,2	<b>N011</b>	<b>N111</b>	CBA 650-40	
.78	19,8	.20	5,1	<b>N041</b>	<b>N141</b>	CBA 780-20	84
.81	20,6	.12	3,0	<b>N024</b>	<b>N124</b>	CBA 810-12	72
<b>CDBA Series</b> Pocket							
.50	12,7	.14	3,6	<b>N018</b>	<b>N118</b>	CDBA 500-14	200
.88	22,4	.40	10,2	<b>N017</b>	<b>N117</b>	CDBA 880-40	72
1.81	46,0	.60	15,2	<b>N030</b>	<b>N130</b>	CDBA 181-60	1
<b>TBA Series</b> Square or Tapered							
.50	12,7	.12	3,0	<b>N009</b>	<b>N109</b>	TBA 5050-12	200
.81	20,6	.30	7,6	<b>N019</b>	<b>N119</b>	TBA 8181-30	98

Standard colors clear and black. For white, gray or brown consult Heyco.


- Quick and easy installation—simply peel off backing and press into place. With no holes to drill, and no screws or rivets needed, adhesive backed bumpers will save you time and money.
- Bumpers can be attached to a wide variety of surfaces; aluminum, ceramic, formica, glass, painted surfaces, polyethylene, polypropylene, vinyl, and steel.
- Adhesive backed bumpers are nonmarking, nonstaining, skid, and scratch resistant.
- Surface must be clean, dry, and free of grease, oil, and other common solvents to obtain maximum adhesion. Clean surfaces with low strength solvents such as Isopropyl Alcohol or Heptane.
- Bumpers have a rubber-based pressure sensitive adhesive with an end use temperature of 0°F (-18°C) to 180°F (82°C).
- Standard colors clear and black. White, gray and brown available, please consult Heyco.




HSA-Hemi



CBA-Cylinder



CDBA-Pocket



TBA-Square or Tapered

Material	Polyurethane
Certifications	Recognized under the Component Program of Underwriters' Laboratories File E196663
Flammability Rating	HB
Temperature Range	0°F (-18°C) to 180°F (82°C)

Quick Specs