

Heyco® Plug-In Device Contacts





PART DATA			PART NO.		
Length in.	AWG Range	Material	Non- polarized	Polarized	Feeds
1.00	Solder	Brass	8063	-	Left to Right
.80	Solder	Brass	8178	-	Bulk
Flat 1.00	Solder	Brass	5029†	5031†	
			5030 ^{††}		
1.28	Solder	Brass	5021	-	
1.30	Solder	Brass	8172	-	
Flat 1.97	Solder	Brass	8191†††	_	
			8192		
	Overall Length in. 1.00 .80 1.00 1.28 1.30	Overall Length in. AWG Range 1.00 Solder .80 Solder 1.00 Solder 1.28 Solder 1.30 Solder	Overall Length in. AWG Range Material 1.00 Solder Brass .80 Solder Brass 1.00 Solder Brass 1.28 Solder Brass 1.30 Solder Brass	Overall Length in. AWG Range Material polarized Non-polarized 1.00 Solder Brass 8063 .80 Solder Brass 8178 1.00 Solder Brass 5029† 1.28 Solder Brass 5021 1.30 Solder Brass 8172 1.97 Solder Brass 8191†††	Overall Length in. AWG Range Material Non-polarized Polarized 1.00 Solder Brass 8063 - 80 Solder Brass 8178 - 1.00 Solder Brass 5029† 5031† 1.28 Solder Brass 5021 - 1.30 Solder Brass 8172 - 1.97 Solder Brass 8191††† -




^{††} Part No. 5030 has straight sides

^{†††} No hole.







8178




5031/5029, 5030



8172





- Designed for cordless OEM products that plug directly into an electrical outlet:
 - Plug-in Transformers
 - Plug-in Electronic Power Supplies
 - Plug-in Electronic Enclosures
 - Plug-in Rodent and Other Pest Control Devices
 - Plug-in Air Fresheners and Insect Repellents
 - Plug-in Smoke and Carbon Monoxide Sensors and Alarms
 - Plug-in Timers
 - Plug-in Night Lights
- Plug-In Contacts are not UL or CSA approved.





Quick Specs

Material

Alloy 260 Brass (70% Cu, 30% Zn. Higher Cu content resists dezincification)