



Custom Male Configurations continued

Listed for Use in the U.S. and Canada Under File E217650

| Part No. | Description | Color | Wire | | Overall Length A in. | ROJ B in. | Strip Length C in. | Ring Terminal Part No. | Strain Relief | |
|-------------------------|--------------|-------|-------------------|-------|----------------------------|-----------------|--------------------------|---------------------------|---------------|----------|
| | | | Gauge AWG/Cond | Type | | | | | Part No. | D in. |
| L5-20P, 14 Gauge | | | | | | | | | | |
| S7613 | T2L 125V-20A | Black | 14-3 | SJT | 36 | 2.5 | 1/2 | 8145 | - | - |
| S7614 | T2L 125V-20A | White | 14-3 | SJT | 36 | 2.5 | 1/2 | 8145 | - | - |
| S7645 | T2L 125V-20A | Black | 14-3 | SEOW | 36 | 2.5 | 1/2 | 8145 | - | - |
| S7646 | T2L 125V-20A | White | 14-3 | SEOW | 36 | 2.5 | 1/2 | 8145 | - | - |
| S7645QQ | T2L 125V-20A | Black | 14-3 | SEOW | 48 | 5 | 1/2 | 8145 | - | - |
| S7645B | T2L 125V-20A | Black | 14-3 | SEOW | 60 | 5 | 1/2 | - | - | - |
| L5-20P, 12 Gauge | | | | | | | | | | |
| S7647BL | T2L 125V-20A | Black | 12-3 | SJTW | 12 | 5 | 1/2 | 8145 | 1865 | 6 |
| S7647BG | T2L 125V-20A | Black | 12-3 | SJTW | 24 | 3.5 | 1/2 | 8145 | 1865 | 4.5 |
| S7642 | T2L 125V-20A | Black | 12-3 | STOW | 36 | 2.5 | 1/2 | 8145 | - | - |
| S7642ZZ | T2L 125V-20A | Black | 12-3 | STOW | 36 | 6 | 1/2 | 8145 | - | - |
| S7647 | T2L 125V-20A | Black | 12-3 | SJTW | 36 | 2.5 | 1/2 | 8145 | - | - |
| S7648 | T2L 125V-20A | White | 12-3 | SJTW | 36 | 2.5 | 1/2 | 8145 | - | - |
| S7647BI | T2L 125V-20A | Black | 12-3 | SJTW | 36 | 6 | 1/2 | - | - | - |
| S7642AA | T2L 125V-20A | Black | 12-3 | STOW | 54 | 6 | 1/2 | - | - | - |
| S7642B | T2L 125V-20A | Black | 12-3 | STOW | 60 | 5 | 1/2 | - | - | - |
| S7642WW | T2L 125V-20A | Black | 12-3 | STOW | 66 | 6 | 1/2 | 8145 | - | - |
| S7642AC | T2L 125V-20A | Black | 12-3 | STOW | 108 | 2.5 | 5/8 | - | - | - |
| L5-30P, 12 Gauge | | | | | | | | | | |
| S7715 | T2L 125V-30A | Black | 12-3 | SJO | 36 | 2.5 | 1/2 | 8145 | - | - |
| S7716 | T2L 125V-30A | Black | 12-3 | SJTO | 36 | 2.5 | 1/2 | 8145 | - | - |
| S7717 | T2L 125V-30A | Black | 12-3 | SJT | 36 | 2.5 | 1/2 | 8145 | - | - |
| L5-30P, 10 Gauge | | | | | | | | | | |
| S7718 | T2L 125V-30A | Black | 10-3 | SJT | 36 | 2.5 | 1/2 | 8145 | - | - |
| S7718BI | T2L 125V-30A | Black | 10-3 | SJT | 36 | 6 | 1/2 | - | - | - |
| L6-15P, 16 Gauge | | | | | | | | | | |
| S7690 | T2L 250V-15A | Black | 16-3 | SE00W | 36 | 2.5 | 1/2 | 8125 | - | - |
| S7690W | T2L 250V-15A | Black | 16-3 | SE00W | 36 | 2.5 | 5/8 | - | - | - |
| S7691 | T2L 250V-15A | White | 16-3 | SEOW | 36 | 2.5 | 1/2 | 8125 | - | - |
| S7691E | T2L 250V-15A | White | 16-3 | SEOW | 36 | 5.5 | 1/2 | 8125 | 1859 | 6.5 |
| S7691W | T2L 250V-15A | White | 16-3 | SEOW | 36 | 2.5 | 5/8 | - | - | - |
| S7691D | T2L 250V-15A | White | 16-3 | SEOW | 42 | 3 | 1/2 | - | - | - |
| S7690G | T2L 250V-15A | Black | 16-3 | SE00W | 72 | 2.5 | 1/2 | 8125 | - | - |
| S7691FF | T2L 250V-15A | White | 16-3 | SEOW | 72 | 2.5 | 5/8 | - | - | - |
| S7691AU | T2L 250V-15A | White | 16-3 | SEOW | 78 | 4 | 1/2 | 8125 | - | - |
| S7691C | T2L 250V-15A | White | 16-3 | SEOW | 78 | 4 | 1/2 | 8125 | 1859 | 6 |
| S7690HH | T2L 250V-15A | Black | 16-3 | SE00W | 84 | 6 | 5/8 | - | - | - |

Don't see the configuration you need?

Consult Heyco for your particular NEMA Plug; wire gauge, type, length, and color; and Strain Relief and Termination requirements. Our Axcell® rapid development team is ready to meet your design requirements.