

**IOVU-07F-AD Dimensions**  
(Unit: mm)

**Options**

Part No.	Description
AFLPK-12	Panel mounting kit
AFLWK-12	VESA 75 wall mounting kit
ARM-11-RS	LCD monitor / PPC arm kit, loading capacity from 3 kg ~ 7 kg
STAND-A08-RS	LCD monitor / PPC stand kit for VESA 75 and supports up to 5 kg
VSTAND-A07	LCD monitor / PPC stand V type for VESA 75, 0~90 degree adjustable hinge and supports up to 2.5 kg
AFLP-CDB01/AFLP-CDW01	VFD customized display (green) 5 x 7 dot matrix (black / white)
63040-010060-030-RS	Adapter Power; FSP; FSP060-DBAE1; 9NA0603111; Active PFC; Vin: 90~264VAC; 60W; Dim:62 x 110 x 31.5mm; Plug=9.5mm; Cable=1500mm; Erp (NO LOAD 0.1W); Vout: 12VDC; Φ2.5/Φ5.5; CCL; RoHS
63040-010060-060-RS	Adapter Power; FSP; FSP060-DBAE1; 9NA0603113; Active PFC; Vin:90~264VAC; 60W; Dim: 62mm x 110mm x 31.5mm; Cable=1200mm; Erp (NO LOAD 0.1W); Vout: 12VDC; Bare Wire; CCL; RoHS

**Packing List**

1 x Utility CD includes application tools, SDK, and technical document

1 x Null modem cable

**Ordering Information**


Part No.	Description
IOVU-07F-AD-ET-R10	7" TFT-LCD; Freescale™ i.MX6 Cortex™-A9 Quad-Core 1.0 GHz CPU; CAN; Android 4.2
IOVU-07F-AD-WBC-R10	7" TFT-LCD; Freescale™ i.MX6 Cortex™-A9 Quad-Core 1.0 GHz CPU; CAN; Wi-Fi/Bluetooth; Camera; Android 4.2



Vehicle PC



Industrial Automation



Home/Building Automation



Multimedia / Digital Signage