

LA Range - Constant Current IP67 LED Drivers



Features:

- Constant Current Driver
- Universal AC Input
- Fully encapsulated to IP67
- Protections: Short Circuit / Over Current
- Small and attractive white case
- Wall Mountable
- 2 Year Warranty

Compliance:

- Magnetic Emissions: EN55015
- Harmonic: EN61000-3-2
- Immunity: EN61547
- Safety: EN61347-1, EN61347-2-13



Model	Input	Output	Suggested Loading	Efficiency (full load)	Dimensions (LxWxH)
LA5-350	100-240Vac	2-12Vdc 350mA	1---3 LED	≥60%	58x28x22mm
LA5-700	100-240Vac	2-7Vdc 700mA	1---2 LED	≥62%	58x28x22mm
LA9-350	100-240Vac	3-24 Vdc 350mA	1---6 LED	≥72%	130x25x21mm
LA9-700	100-240Vac	2-12Vdc 700mA	1---3 LED	≥72%	130x25x21mm
LA20-350	100-240Vac	9-48Vdc 350mA	3---13 LED	≥82%	140x30x20mm
LA20-700	100-240Vac	3-28Vdc 700mA	1---8 LED	≥82%	140x30x20mm
LA35-350	100-240Vac	30-80Vdc 350mA	9---22 LED	≥85%	148x32x26mm
LA35-700	100-240Vac	9-48Vdc 700mA	3---13 LED	≥85%	148x32x26mm
LA35-1050	100-240Vac	9-30Vdc 1050mA	3---8 LED	≥85%	148x32x26mm
LA35-1400	100-240Vac	9-24Vdc 1400mA	3---6 LED	≥85%	148x32x26mm
LA50-700	100-240Vac	30-72Vdc 700mA	9---20 LED	≥86%	148x40x30mm
LA50-1050	100-240Vac	9-48Vdc 1050mA	3---13 LED	≥86%	148x40x30mm
LA50-1400	100-240Vac	9-36Vdc 1400mA	3---10 LED	≥86%	148x40x30mm
LA60-1050	100-240Vac	12-60Vdc 1050mA	4--- 16 LED	≥87%	162x42.5x30mm
LA60-1400	100-240Vac	9-42Vdc 1400mA	3---12 LED	≥87%	162x42.5x30mm
LA60-1750	100-240Vac	9-36Vdc 1750mA	3---10 LED	≥87%	162x42.5x30mm

Custom & Bespoke LED Drivers

Stontronics also offers design consultancy and bespoke options on top of all its standard models. For example we have the facility to offer:

- Extended warranties (up to 5 years),
- Custom output voltages for our constant voltage drivers,
- Custom current ratings for our constant current drivers,
- Bespoke case design and different form factors,
- Custom flying lead lengths and output connectors,
- Re-labelling service for customer brands,
- Shorter lead times by using air-freight instead of standard sea-freight,
- Retail, standard, bulk or other forms of packaging,
- Extensive test reports and additional certification for independent test bodies on request.

Please Note that bespoke options incur minimum order quantities. To find out more please contact the sales team now:

Email: sales@stontronics.co.uk or info@stontronics.co.uk

Tel: +44 (0) 118 931 1199

Fax: +44 (0) 118 931 1145

Address: Chancerygate Business Centre,
Cradock Road,
Reading,
Berkshire,
RG2 0AH
United Kingdom



Quad Output C.C.



Open Frame Variants



Internal & External



Dimmable type



Custom Voltage & Current

