




- Features :
- 2:1 wide input range
 - 4:1 wide input range(optional)
 - 1000VDC I/O isolation
 - 3000VDC I/O isolation (option)
 - Input Pi network filter
 - Protections: Short circuit/ Over load
 - Free air convection
 - Five-sided shield metal case
 - High reliability / Low cost
 - 100% burn-in test
 - 1 year warranty

SPECIFICATION

ORDER NO.	DLW05A-05	DLW05B-05	DLW05C-05	DLW05A-12	DLW05B-12	DLW05C-12	DLW05A-15	DLW05B-15	DLW05C-15	
OUTPUT	DC VOLTAGE	±5V			±12V			±15V		
	CURRENT RANGE	±50 ~ ±500mA			±20.8 ~ ±208mA			±16.7 ~ ±167mA		
	RATED POWER	5W								
	RIPPLE & NOISE (max.) ^{Note.2}	50mVp-p			60mVp-p			60mVp-p		
	LINE REGULATION ^{Note.3}	±0.2%								
	LOAD REGULATION ^{Note.4}	±0.5%								
	VOLTAGE ACCURACY	±2.0%								
	SWITCHING FREQUENCY	50KHz min.								
INPUT	VOLTAGE RANGE	A: 9 ~ 18VDC B: 18~36VDC C: 36~72VDC								
	EFFICIENCY (Typ.)	75%	77%	77%	80%	82%	83%	81%	83%	85%
	DC CURRENT	Full load	A: 556mA B: 270mA C: 135mA							
	No load	A: 33mA B: 16mA C: 10mA								
FILTER	Pi network									
PROTECTION (Note. 5)	OVER LOAD	160~250% rated output power Protection type : Hiccup mode, recovers automatically after fault condition is removed								
	SHORT CIRCUIT	All output equipped with short circuit Protection type : Hiccup mode, recovers automatically after fault condition is removed								
ENVIRONMENT	WORKING TEMP.	-25~+71°C (Refer to output load derating curve)								
	WORKING HUMIDITY	20%~90% RH non-condensing								
	STORAGE TEMP., HUMIDITY	-25~+105°C, 10~95% RH								
	TEMP. COEFFICIENT	±0.03% / °C (0~50°C)								
	VIBRATION	10~500Hz, 2G 10min./1 cycle, period for 60min. each along X, Y, Z axes								
SAFETY & EMC	WITHSTAND VOLTAGE	I/P-O/P:1KVDC								
	ISOLATION RESISTANCE	I/P-O/P: 100M Ohms / 500VDC								
OTHERS	MTBF	800khrs min. MIL-HDBK-217F(25°C)								
	DIMENSION	50.8*25.4*11.27mm or 2.0**1.0**0.44" inch (L*W*H)								
	WEIGHT	32g								


■ Mechanical Specification



■ Pin Configuration

Pin no.	Output Dual
1	+Vin
2	-Vin
3	+Vout
4	COM
5	-Vout

■ Derating Curve



NOTE

- 1.All parameters are specified at normal input, rated load, 25°C 70% RH. Ambient.
- 2.Ripple & noise are measured at 20MHz by using a 12" twisted pair terminated with a 0.1uf & 47uf capacitor.
- 3.Line regulation is measured from low line to high line at rated load.
- 4.Load regulation is measured from 10% to 100% rated load.
- 5.Please prevent the converter from operating in overload or short circuit condition for more than 30 seconds.