



- Single / Dual / Triple Outputs
- Universal 90 to 264VAC Input
- 3.3Volts(DC) to 48Volts(DC) Outputs
- 4242VDC Input to Output Isolation
- PCB and Chassis Mount Packages
- Full Safety Approvals



Fully Approved

Model Number	Output Voltage	Output Amps	Output Watts	Load Regulation	Efficiency	Ripple & Noise
--------------	----------------	-------------	--------------	-----------------	------------	----------------

SINGLE OUTPUT - PCB Mount

ESCA-0300	3.3 Volts(DC)	7.5 Amps	25W	3% max.	73%, typ.	150mV p-p max.
ESCA-0301	5 Volts(DC)	6 Amps	30W	2% max.	78%, typ.	150mV p-p max.
ESCA-0322	9 Volts(DC)	3.33 Amps	30W	1% max.	81%, typ.	150mV p-p max.
ESCA-0302	12 Volts(DC)	2.5 Amps	30W	1% max.	83%, typ.	150mV p-p max.
ESCA-0303	15 Volts(DC)	2 Amps	30W	1% max.	84%, typ.	150mV p-p max.
ESCA-0318	18 Volts(DC)	1.67 Amps	30W	1% max.	84%, typ.	150mV p-p max.
ESCA-0305	24 Volts(DC)	1.25 Amps	30W	1% max.	84%, typ.	150mV p-p max.
ESCA-0312	48 Volts(DC)	0.63 Amps	30W	1% max.	85%, typ.	150mV p-p max.

SINGLE OUTPUT - Chassis Mount

ESCC-0300	3.3 Volts(DC)	7.5 Amps	25W	3% max.	73%, typ.	150mV p-p max.
ESCC-0301	5 Volts(DC)	6 Amps	30W	2% max.	78%, typ.	150mV p-p max.
ESCC-0322	9 Volts(DC)	3.33 Amps	30W	1% max.	81%, typ.	150mV p-p max.
ESCC-0302	12 Volts(DC)	2.5 Amps	30W	1% max.	83%, typ.	150mV p-p max.
ESCC-0303	15 Volts(DC)	2 Amps	30W	1% max.	84%, typ.	150mV p-p max.
ESCC-0318	18 Volts(DC)	1.67 Amps	30W	1% max.	84%, typ.	150mV p-p max.
ESCC-0305	24 Volts(DC)	1.25 Amps	30W	1% max.	84%, typ.	150mV p-p max.
ESCC-0312	48 Volts(DC)	0.63 Amps	30W	1% max.	85%, typ.	150mV p-p max.

SINGLE OUTPUT - DIN Rail Mount

ESCC-0300/DRL	3.3 Volts(DC)	7.5 Amps	25W	3% max.	73%, typ.	150mV p-p max.
ESCC-0301/DRL	5 Volts(DC)	6 Amps	30W	2% max.	78%, typ.	150mV p-p max.
ESCC-0322/DRL	9 Volts(DC)	3.33 Amps	30W	1% max.	81%, typ.	150mV p-p max.
ESCC-0302/DRL	12 Volts(DC)	2.5 Amps	30W	1% max.	83%, typ.	150mV p-p max.
ESCC-0303/DRL	15 Volts(DC)	2 Amps	30W	1% max.	84%, typ.	150mV p-p max.
ESCC-0318/DRL	18 Volts(DC)	1.67 Amps	30W	1% max.	84%, typ.	150mV p-p max.
ESCC-0305/DRL	24 Volts(DC)	1.25 Amps	30W	1% max.	84%, typ.	150mV p-p max.
ESCC-0312/DRL	48 Volts(DC)	0.63 Amps	30W	1% max.	85%, typ.	150mV p-p max.



- Single / Dual / Triple Outputs
- Universal 90 to 264VAC Input
- 3.3Volts(DC) to 24Volts(DC) Outputs
- 4242VDC Input to Output Isolation
- PCB and Chassis Mount Packages
- Full Safety Approvals



Fully Approved

Model Number	Output Voltage	Output Amps	Output Watts	Load Regulation	Ripple & Noise	Efficiency
--------------	----------------	-------------	--------------	-----------------	----------------	------------

DUAL OUTPUT - PCB Mount

EDCA-0306	±12 Volts(DC)	±1.25 Amps	30W	±3% max.	±100mV p-p max.	80%, typ.
EDCA-0307	±15 Volts(DC)	±1 Amps	30W	±3% max.	±100mV p-p max.	80%, typ.
EDCA-0308	+5/12 Volts(DC)	3/1.25 Amps	30W	±2 / ±4% max.	100 / 150mV p-p max.	74%, typ.

DUAL OUTPUT - Chassis Mount

EDCC-0306	±12 Volts(DC)	±1.25 Amps	30W	±3% max.	±100mV p-p max.	80%, typ.
EDCC-0307	±15 Volts(DC)	±1 Amps	30W	±3% max.	±100mV p-p max.	80%, typ.
EDCC-0308	+5/12 Volts(DC)	3/1.25 Amps	30W	±2 / ±4% max.	100 / 150mV p-p max.	74%, typ.

DUAL OUTPUT - DIN Rail Mount

EDCC-0306/DRL	±12 Volts(DC)	±1.25 Amps	30W	±3% max.	±100mV p-p max.	80%, typ.
EDCC-0307/DRL	±15 Volts(DC)	±1 Amps	30W	±3% max.	±100mV p-p max.	80%, typ.
EDCC-0308/DRL	+5/12 Volts(DC)	3/1.25 Amps	30W	±2 / ±4% max.	100 / 150mV p-p max.	74%, typ.

TRIPLE OUTPUT - PCB Mount

ETCA-0309	+5,±12 Volts(DC)	3,0.63/0.63 Amps	30W	0.6 / ±0.5% max.	100, ±75mV p-p max.	74%, typ.
ETCA-0311	+5,±15 Volts(DC)	3,0.5/0.5 Amps	30W	0.6 / ±0.5% max.	100, ±75mV p-p max.	74%, typ.

TRIPLE OUTPUT - Chassis Mount

ETCC-0309	+5,±12 Volts(DC)	3,0.63/0.63 Amps	30W	0.6 / ±0.5% max.	100, ±75mV p-p max.	74%, typ.
ETCC-0311	+5,±15 Volts(DC)	3,0.5/0.5 Amps	30W	0.6 / ±0.5% max.	100, ±75mV p-p max.	74%, typ.

TRIPLE OUTPUT - DIN Rail Mount

ETCC-0309/DRL	+5,±12 Volts(DC)	3,0.63/0.63 Amps	30W	0.6 / ±0.5% max.	100, ±75mV p-p max.	74%, typ.
ETCC-0311/DRL	+5,±15 Volts(DC)	3,0.5/0.5 Amps	30W	0.6 / ±0.5% max.	100, ±75mV p-p max.	74%, typ.

30W Ultraminiature Encapsulated Switching Power Supplies

ECA30 series


INPUT SPECIFICATIONS

Input Voltage, Nominal	90-264VAC
	Nominal: 100-240VAC
Input Frequency	47-63 Hz, 50-60Hz Nom.
Inrush Current	30A @ 115VAC, typ
	60A @ 230VAC, typ

OUTPUT SPECIFICATIONS

Output Voltage/Current	See Specific Model
Preset Accuracy	±1% (±2 / ±5% -0308)
Triples:	1%, ±5%
Load Regulation	See Specific Model
Line Regulation	±1%, max.
Triples:	0.6%, ±0.2%
Temperature Coefficient	±0.03%/°C
Ripple/Noise(20Mhz BW)	See Specific Model
Oversoltage Protection	Latching, Auto Recovery *
Hold Up Time	20mS, typ
Short Circuit Protection	Latching, Auto Recovery *
Current Limit	>110% of Full Scale, Power Limit

DERATE CURVE



All specifications are typical at nominal input, full load, and 25DegC unless otherwise noted

* These are stress ratings. Exposure of the devices to any of these conditions may adversely affect long term reliability. Proper operation under conditions other than the standard operating conditions is neither warranted nor implied.

GENERAL SPECIFICATIONS

Isolation	4242VDC Input-Output
Switching Frequency	65 Khz, fixed
Efficiency (@ Full Load)	See Specific Model
Safety	UL60950-1, EN60950-1


ENVIRONMENTAL SPECIFICATIONS

Oper. Temperature	0 to +50°C FL See Derate *
	(Free-air Convection)
Relative Humidity	0-95%, Non-Condensing
Storage Temperature	-25 to +71°C *
EMC	EN55022, Class II


PHYSICAL SPECIFICATIONS

Case Material	Rynite, 94V-0 Rated
Construction	Encapsulated,
Size PCB Mount	Single O/P: 3.5" x 2.5" x 0.98"
	Multi O/P: 4.06" x 2.5" x 0.98"
Chassis Mount	Single O/P: 4.76" x 2.56" x 1.0"
	Multi O/P: 5.34" x 2.56" x 1.0"
Weight PCB / CHASSIS Mount	
Singles	10.4 oz (292g) / 13.4 oz (376g)
Duals/Triples	12.1 oz (340g) / 15.4 oz (430g)


MECHANICAL DIMENSIONS - PCB MOUNT



SINGLE OUTPUT




DUAL/TRIPLE OUTPUT




Model Type / Pin#	Single	Dual Matched	Dual 5/12V	Dual Triple
1	AC HI	AC HI	AC HI	AC HI
2	AC LO	AC LO	AC LO	AC LO
3	No Pin	-Vout	Com	-Vout
4	No Pin	No Pin	No Pin	No Pin
5	No Pin	No Pin	No Pin	+5 Ret
6	-Vout	Com	+5out	+/-Com
7	No Pin	No Pin	No Pin	+5Vout
8	+Vout	+Vout	+12Vout	+Vout

MECHANICAL DIMENSIONS - CHASSIS MOUNT



MECHANICAL DIMENSIONS - DIN RAIL



Model Type / Pin#	Single	Match Dual	Unmatch Dual	Triple
1	AC LO	AC LO	AC LO	AC LO
2	N/C	N/C	N/C	N/C
3	AC HI	AC HI	AC HI	AC HI
4	+Vout	+Vout	+12Vout	+Vout
5	+Vout	Com	+5Vout	+5Vout
6	-Vout	Com	+5Vout	+/- Com
7	-Vout	-Vout	Com	+5V Ret
8	N/C	N/C	Com	-Vout
9	N/C	N/C	N/C	N/C

DIN Rail mounting kit available for Chassis-mount modules.
 - For 30 watt single outputs specify part # M-DRL-30S
 - For 30 watt dual/single outputs specify part # M-DRL-30T
 Kit includes mounting plate, DIN Rail cliip and assembly hardware.