



Smart Technology. Delivered.

Dual Band 2400-2500 MHz/5150-5875 MHz 6-port MIMO Pole/Mast Mount Antenna

OP24516DS



6-PORT OMNIDIRECTIONAL DUAL BAND MIMO ANTENNA

The OP24516DS antenna is an indoor/outdoor pole mounted omnidirectional antenna designed for 802.11n applications. As a 6-element MIMO antenna, each port operates over the 2.4GHz and 5 GHz bands, providing a broadband solution in a single radome. It features a low profile radome and is designed to withstand the rigors of outdoor applications with an IP67 Ingression Protection rating. The radiation patterns are uniform and symmetrical, providing high levels of signal density into defined coverage zones. This antenna greatly enhances the performance of 802.11n systems.

FEATURES

- Low profile esthetically neutral housing
- Both indoor/outdoor
- 6-element MIMO solution
- IP67 rating
- Conformance to RoHS

MARKETS

- Offices, hotels and college campuses
- Airports and hospitals
- Bus terminals and train stations
- Museums, libraries and retail malls
- Wi-Fi Hot Spots
- Cellular off-loading
- 802.11n MIMO

PARAMETER	PERFORMANCE
Frequency	2400-2500 MHz/5150-5875 MHz
Gain (dBi)	2.0 Typical (2.8 Max)/ 4.8 Typical (6.5 Max)
VSWR	2.0:1, Max
Nominal Impedance	50Ω
Polarization	Linear, Vertical
Azimuth Typical 3dB Beamwidth	Omnidirectional
Elevation Typical 3dB Beamwidth	66° /30°
Port-to-Port Isolation	20 dB /25 dB
Input Power	5W x 6
RF Connector	Type N, Male 6x
Cable Type	Plenum rated RG-58
Cable Length	910 mm±18 mm 6x (36 in±0.71 in 6x)
Radome Material	Polycarbonate, White
Mounting	Mast Mount (31.8-57.2 OD)
Wind Survival	200 km/hr (125 mph)
Operational Temperature	-30°C to +70°C
Storage Temperature	-40°C to +85°C
Ingression Protection	IP67
Dimensions (height x OD)	116.5 x 209.6 mm
Weight	1.6 kg (3.53 lbs)

CONNECTORS

Part No.	Connector
OP24516DS-91NM	Type N male
OP24516DS-91RSMM	Reverse Polarity SMA male

Americas: +1.847 839.6907
IAS-AmericasEastSales@lairdtech.com


Europe: +44.1628.858941
IAS-EUSales@lairdtech.com

Asia: +86.21.5855.0827.127
IAS-AsiaSales@lairdtech.com


www.lairdtech.com

Dual Band 2400-2500 MHz/5150-5875 MHz 6-port MIMO Pole/Mast Mount Antenna OP24516DS


AZIMUTH PATTERNS



Port 1




Port 2




Port 3


Frequency = 2400 MHz



Port 1




Port 2




Port 3

Frequency = 5550 MHz


ELEVATION PATTERNS



Port 1




Port 2




Port 3


Frequency = 2400 MHz



Port 1



Port 2



Port 3

Frequency = 5550 MHz

Americas: +1.847.839.6907
IAS-AmericasEastSales@lairdtech.com

Europe: +44.1628.858941
IAS-EUSales@lairdtech.com

Asia: +86.21.5855.0827.127
IAS-AsiaSales@lairdtech.com

www.lairdtech.com

ANT-DS-OP24516DS 0315

Any information furnished by Laird Inc. and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird materials rests with the end user, since Laird and its agents cannot be aware of all potential uses. Laird makes no warranties as to the fitness, merchantability or suitability of any Laird materials or products for any specific or general uses. Laird shall not be liable for incidental or consequential damages of any kind. All Laird products are sold pursuant to the Laird Terms and Conditions of sale in effect from time to time, a copy of which will be furnished upon request. © Copyright 2015 Laird Inc. All Rights Reserved. Laird, Laird Technologies, the Laird Logo, and other marks are trade marks or registered trade marks of Laird Inc. or an affiliate company thereof. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird or any third party intellectual property rights.