



### 800/900 MHz OMNIDIRECTIONAL ANTENNAS

Omnidirectional antennas are the right choice for situations where you need to be in contact with sources that are in two directions or if you do not know what direction the signals will be coming from.

Standard data transmission omnis are fully decoupled antennas built on a copper laminate and housed in 0.100 inch wall fiberglass housings. They may be mounted right side up or tipped side down depending upon the desired pattern. They also feature a very versatile clamp mounting system that will fit most every situation you will encounter.


#### FEATURES

- Fiberglass enclosures
- Plated copper laminated radiator
- Weatherproof designs with UltraLink pigtail
- Broadband performance
- DC grounded
- Omnidirectional

#### MARKETS

- WiMAX

#### ANTENNA PATTERNS



#### global solutions: local support.™

Americas: +1.847.839.6907  
IAS-AmericasEastSales@lairdtech.com

Europe: +1.32.80.7866.12  
IAS-EUSales@lairdtech.com

Asia: +1.65.6.243.8022  
IAS-AsiaSales@lairdtech.com

[www.lairdtech.com](http://www.lairdtech.com)

### SPECIFICATIONS

MODEL	FREQ. MHz	VSWR (NOMINAL)	BANDWIDTH 1.5:1 MHz	-3 dB BWWIDTH E-PLANE	TYPE (FEMALE)	HEIGHT in(cm)	WEIGHT lb(kg)	W/SUR AREA ft <sup>2</sup> (m <sup>2</sup> )	W/SURVIVAL mph(kph)	PIGTAIL in(cm)
S8964B	896-960	1.5:1	64	25°	N	42-1/8 (107)	1.56 (0.70)	0.22 (0.02)	125 (200)	23
S8963B	896-960	1.5:1	64	45°	N	30-3/4 (78)	1.19 (0.53)	0.176 (0.016)	125 (200)	23
S8960B	896-960	1.5:1	64	75°	N	17-1/2 (44.5)	0.56 (0.25)	0.083 (0.009)	125 (200)	17
S8804B	880-960	1.5:1	62	25°	N	42-1/8 (107)	1.56 (0.70)	0.22 (0.02)	125 (200)	23
S8803B	880-960	1.5:1	62	45°	N	30-3/4 (78)	1.19 (0.53)	0.176 (0.016)	125 (200)	23
S8800B	880-960	1.5:1	62	75°	N	17-1/2 (44.5)	0.56 (0.25)	0.083 (0.009)	125 (200)	17
S8244B	824-896	1.5:1	62	25°	N	42-1/8 (107)	1.56 (0.70)	0.22 (0.02)	125 (200)	23
S8243B	824-896	1.5:1	62	45°	N	30-3/4 (78)	1.19 (0.53)	0.176 (0.016)	125 (200)	23
S8240B	824-896	1.5:1	62	75°	N	17-1/2 (44.5)	0.56 (0.25)	0.083 (0.009)	125 (200)	17
S8064B	806-868	1.5:1	62	25°	N	42-1/8 (107)	1.56 (0.70)	0.22 (0.02)	125 (200)	23
S8063B	806-868	1.5:1	62	45°	N	30-3/4 (78)	1.19 (0.53)	0.176 (0.016)	125 (200)	23
S8060B	806-868	1.5:1	62	75°	N	17-1/2 (44.5)	0.56 (0.25)	0.083 (0.009)	125 (200)	17

Common specifications: Power handling - 150 watts; Element material - plated copper laminate; Enclosure material - fiberglass; Mounting style - tube end; Maximum mast diameter - 2 in (5.1 cm)

#### ANT-DS-S8xxxB 0611

Any information furnished by Laird Technologies, Inc. and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird Technologies materials rests with the end user, since Laird Technologies and its agents cannot be aware of all potential uses. Laird Technologies makes no warranties as to the fitness, merchantability or suitability of any Laird Technologies materials or products for any specific or general uses. Laird Technologies shall not be liable for incidental or consequential damages of any kind. All Laird Technologies products are sold pursuant to the Laird Technologies' Terms and Conditions of sale in effect from time to time, a copy of which will be furnished upon request. © Copyright 2011 Laird Technologies, Inc. All Rights Reserved. Laird, Laird Technologies, the Laird Technologies Logo, and other marks are trade marks or registered trade marks of Laird Technologies, Inc. or an affiliate company thereof. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird Technologies or any third party intellectual property rights.