



Smart Technology. Delivered.

Asset Tracking External Antenna

1575 MHz|GPS



LOW-COST ANTENNA IS IDEAL IN RUGGED CONDITIONS

Laird's low-cost GPS antenna is designed to receive GPS broadcast. The GPS magnet mount car antenna specifications are based on a one-meter ground plane. This high-volume, low-cost product meets automotive specifications for durability and quality.

Laird is a leading supplier of vehicular & GPS antenna solutions to the public safety, land mobile radio, and asset tracking industries. Antennas offered range from VHF to 5 GHz, with various multiband offerings; form factors include whip style or low profile.

FEATURES

- Small footprint - very low profile
- IP67 rated
- RG-174, with multiple connector options available
- Grommet over mold allows for better cable stability
- Rubber splint to route cable directly in edge-of-roof applications
- Label and liner can be modified to meet the needs of the customer
- Magnetic and/or adhesive; magnetic base with a double-sided adhesive foam gasket

BENEFITS

- Low total-cost implementation
- Easy installation
- Small package size
- Meets enhanced environmental specifications

APPLICATIONS

- General automotive aftermarket
- Fleet logistics, tracking, and diagnostics
- Theft protection
- Vehicle and asset recovery
- Navigation systems
- Infotainment systems
- On-board computing

Americas: +1.847.839.6907
IAS-AmericasEastSales@lairdtech.com

Europe: +44.1628.858941
IAS-EUSales@lairdtech.com

Asia: +86.21.5855.0827.127
IAS-AsiaSales@lairdtech.com

www.lairdtech.com



Smart Technology. Delivered.

Asset Tracking External Antenna 1575 MHz|GPS

External GPS

ANTENNA SPECIFICATION

frequency Range	1574.42-1576.42 MHz
Peak Gain	4.0 dBic max @ Boresight
Polarization	RHCP
Impedance	50 W
Output VSWR (Min. performance)	≤ 2:1

LNA SPECIFICATION

gain (Max)	29 dB
Noise Figure	≤1.5 dB
Supply Voltage	3.3 ± 0.3V or 5.0 ± 0.5V
Current	25 mA
Input P1dB	≥-27dBm
Output VSWR	≤ 2:1

MECHANICAL SPECIFICATION

Dimension	44 x 36 x 14mm
Radome Material	Black ASA+pC (Luran S 778T)
Cable Length	7010mm
Cable Type	RG-174
Mounting Method	Magnetic and/or Adhesive

ENVIRONMENTAL SPECIFICATION

Operating Temperature	-40 C to +85 C
Humidity	Operation 95% RH at 65oC
Ingress Protection	IP67 Rated
Drop Test / Shock	50 g shocks 10x3 axis / 1 meter drop 6 axis
Vibration	10-1000 Hz vibration 1 hour 3 axis

ORDERING INFORMATION

Model #	Connector
GPS15MG-MMCX-M	MMCX
GPS15MG SMA	SMA
GPS15MG SMB	SMB
GPS15MG TNC	TNC



Magnetic Base

Americas: +1.847 839.6907
IAS-AmericasEastSales@lairdtech.com

Europe: +44.1628.858941
IAS-EUSales@lairdtech.com

Asia: +86.21.5855.0827.127
IAS-AsiaSales@lairdtech.com

www.lairdtech.com

IAS-DS-EXTERNAL-GPS 0115

Any information furnished by Laird Inc. and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird materials rests with the end user, since Laird and its agents cannot be aware of all potential uses. Laird makes no warranties as to the fitness, merchantability or suitability of any Laird materials or products for any specific or general uses. Laird shall not be liable for incidental or consequential damages of any kind. All Laird products are sold pursuant to the Laird Terms and Conditions of sale in effect from time to time, a copy of which will be furnished upon request. © Copyright 2015 Laird Inc. All Rights Reserved. Laird, Laird Technologies, the Laird Logo, and other marks are trademarks or registered trademarks of Laird Inc. or an affiliate company thereof. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird or any third party intellectual property rights.