



注記
NOTE

- 1 ウエハーのそりは、長さ 25.4 に対して 0.24 MAX..
CAMBER MUST BE 0.24 MAX. PER 25.4
- △ 全極数が偶数の場合のみ適用。
TO BE APPLIED ONLY WHEN ALL CKTS. ARE EVEN.

49.72	45.72	10-32-1101	5281-10A	10
44.64	40.64	↑ -109I	↑ -09A	9
39.56	35.56	↑ -108I	↑ -08A	8
34.48	30.48	↑ -107I	↑ -07A	7
29.4	25.4	↑ -106I	↑ -06A	6
24.32	20.32	↑ -105I	↑ -05A	5
19.24	15.24	↑ -104I	↑ -04A	4
14.16	10.16	↑ -103I	↑ -03A	3
9.08	5.08	10-32-1021	5281-02A	2
B	A	EDP NO.	ENG. NO.	極数 NO. OF CKTS.

REVISED EC NO: J2014-1442 DRWN: TYAJIMA01 2014/03/25 CHKD: KASAKAWA 2014/03/26 APPR: NUKITA 2014/03/26	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE MM ONLY		SCALE 4:1	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION	
	10 UNDER	± 0.15	DRAWN BY TYAJIMA01	DATE 2014/03/13	TITLE KK 5.08 WAFER ASSY WITH LOCK			
	10 OVER 30 UNDER	± ---	CHECKED BY KASAKAWA	DATE 2014/03/13				
	30 OVER	± ---	APPROVED BY NUKITA	DATE 2014/03/13	molex SD-5281-001			
ANGULAR ± 1 °		MATERIAL NO. SEE DRAWING		DOCUMENT NO.				
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION						