



NOTES:

1. TERMINAL FOR USE WITH HOUSING PART NO. 70066-**** & 70107-****.
2. MATERIAL: .008/(0.20) THK. PHOSPHOR BRONZE.
3. TERMINAL TO BE USED WITH 22-24 AWG STRANDED WIRE WITH .064 DIA. MAX. INSULATION.
4. REFER TO MOLEX OPERATIONAL AND SERVICE MANUAL FOR DETAILS.
5. REFER TO PRODUCT SPECIFICATION NO. PS-70021.
6. PARTS SUPPLIED IN REEL FORM.

PLATING:

.000030 GOLD PLATE IN SELECT AREA.
 .000075 MIN. TIN PLATE IN SELECT AREA.
 OVER NICKEL PLATE.

*THE PRIMARY SHIPPING CARTON WILL BE LABELED "COMPLIANT TO RoHS DIRECTIVE 2002/95/EC AND ELV ANNEX II OF DIRECTIVE 2000/53/EC". CARTONS WITHOUT THIS LABEL MAY CONTAIN PRODUCT WITH LEAD.

| | |
|----|--|
| E | LEAD FREE UCP2004-1769 RWHITE 04/03/12 |
| D1 | REVISED ECR #U80270 MCGRATH 97/07/31 |
| D | REVISED PLTG. SPEC. PER ECR # U31149 08/19/93 REED |
| C | REVISED PER ECR# U82220 11-07-88 MJM/MGB |
| B | REDRAWN ON CAD PER E.C.R. #9509 11/10/86 WJF/MJM |

| | | | |
|----------|------|------|-----------|
| MFG. SH. | REV. | LTR. | REVISIONS |
|----------|------|------|-----------|

| | | | | | |
|---|--------|--------------------------|--|--|--|
| DIMENSIONS SHOWN (METRIC): INCH | | ▽ = 0 ▼ = 0 | | REVISE ONLY ON CAD SYSTEM | |
| UNLESS OTHERWISE SPECIFIED TOLERANCES: ANGULAR ± 1/2° | | | | | |
| | | INCH | | METRIC | |
| 3 PLACE | ± .010 | --- | | | |
| 2 PLACE | ± .015 | ± 0.25 | | | |
| 1 PLACE | --- | ± 0.35 | | | |
| DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS | | | | | |
| DRWG. BY: WJF | | CHK'D. BY: MJM | | FILE NAME: S70021X25 DGN | |
| APP'D. BY: WAZ | | SCALE: 10:1 | | THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INC. AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION. | |
| MOLEX INCORPORATED | | LISLE, ILL. 60532 U.S.A. | | SHEET NO. 1 DATE 10/30/86 | |
| PART NO. 16-02-0116 | | DRWG. NO. SD-70021-0025 | | DIV. DA SIZE B | |

TERMINAL, MALE CRIMP