



回路番号1
CKT. NO. 1

キャビティ番号
CAV. NO.

トレードマーク
TRADE MARK

NOTES

- 適合ターミナル : 502438-0*00
APPLICABLE TARMINAL : 502438-0*00
- 嵌合相手 : 502443-**70,502494-**70
MATE WITH : 502443-**70,502494-**70
- 極数/2 = 偶数に適応
APPLY FOR CKT. SIZE /2 = EVEN.
- 本製品のプラスチック部に黒点等が確認される場合や色合いが異なる場合がありますが、製品性能に影響はありません。
THERE IS NO INFLUENCE IN THE PRODUCT PERFORMANCE THOUGH THE BLACK SPOT ETC. MIGHT BE CONIRMED TO THE PLASTIC PART OF THIS PRODUCT AND THE SHADE MIGHT BE DIFFERENT.
- アプリケーション仕様書(コネクタ取扱い説明書) : AS-502439-001
APPLICATION SPECIFIONS (CONNECTOR MANNUAL):AS-502439-001
- 製品仕様書:5024431570PS000
PRODUCT SPECIFICATION : 5024431570PS000
- ELV 及び RoHS 適合品
ELV AND RoHS COMPLIANT

28	34	502439-1500	15
26	32	502439-1400	14
24	30	502439-1300	13
22	28	502439-1200	12
18	24	502439-1000	10
16	22	502439-0900	9
14	20	502439-0800	8
12	18	502439-0700	7
10	16	502439-0600	6
8	14	502439-0500	5
6	12	502439-0400	4
4	10	502439-0300	3
2	8	502439-0200	2
B	A	製品番号 MATERIAL NO.	極数 CKT.NO.

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

REDRAWN AND REVISED EC NO: 104566 DRWN: AISHIKAWA CHK'D: KOMURAKAMI REV APPR: TKANEKO	2016/04/19	GENERAL TOLERANCES (UNLESS SPECIFIED)	DIMENSION UNITS	SCALE		
	2016/04/28	ANGULAR TOL ± 3.0 °	MM	4:1		
		4 PLACES ± 0.2	DRWN BY	DATE		AISHIKAWA 2016/04/19
		3 PLACES ± 0.2	CHK'D BY	DATE		KOMURAKAMI 2016/04/28
	2 PLACES ± 0.2	2 PLACES ± 0.2	APPR BY	DATE	TKANEKO 2016/04/28	
	1 PLACE ± 0.2	1 PLACE ± 0.2	DRAWING SIZE	THIRD ANGLE PROJECTION		
	0 PLACES ± 0.2	0 PLACES ± 0.2	A3			
		DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS				

CLIK-MATE 2.0MM PITCH
W/B CONN. SINGLE PLUG HSG

PRODUCT CUSTOMER DRAWING

SERIES	MATERIAL NUMBER	CUSTOMER
502439	SEE TABLE	GENERAL
DOCUMENT NUMBER	DOC TYPE	DOC PART
5024391500	PSD	000
SHEET NUMBER	1 OF 1	

部品 PART	材質 MATERIAL
ハウジング HOUSING	ポリブチレンテレフタレート UL94V-0 色 : 白 POLYBUTYLENE TEREPHTHALATE UL94V-0 COLOR:WHITE
RELEASE STATUS	P1
RELEASE DATE	28.04.2016 09:56:04