



LOCKING SERRATIONS PREVENT LOOSE CONNECTIONS CAUSED BY VIBRATION.

MULTI-STUD HOLE SIZE SEE CHART

- NOTES:
1. CONDUCTOR MAT'L: COPPER
PLATING: TIN
 2. FUNNEL FERRULE: BRASS
PLATING: TIN
 3. NYLON INSULATION: COLOR CODED
SEE CHART

STUD HOLE SIZES:	
06	= .146
08	= .173
10	= .198

A	UPDATE BORDER CHANGE "L" DIM. ETC70785 04/07 JH
LTR.	REVISIONS

CUSTOMER DRAWING

REVISE ONLY ON CAD SYSTEM

DIMENSIONS SHOWN (METRIC) INCH			
UNLESS OTHERWISE SPECIFIED TOLERANCES: ANGULAR ± 1/2°			
	INCH	METRIC	
3 PLACE	± .005	± ---	
2 PLACE	± .01	± 0.13	
1 PLACE	± ---	± 0.25	

DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

DRWG. BY	EMF	CHK'D. BY	RWD
APP'D. BY	RWD	SCALE	NO:NE

TITLE		SHEET NO.		DATE	
VIBRAKRIMP MULTI-STUD RING TONGUE TERMINAL				93/02/22	
PART NO.		DRWG. NO.			
SEE TABLE		MSRINGCD			
THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX-ETC INC. AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.				DIV. SIZE	
				B	

MWID = MAX. WIRE INSULATION DIA.
PART NUMBERS ARE FOR LOOSE PIECE TO ORDER PARTS ON TAPE ADD A "T" TO END OF PART NUMBER

PART NUMBER	WIRE RANGE AWG	INSUL. COLOR	"L" MAX.	"W" MAX.	"C" MIN.	"C" MAX.	"D" MIN.	MWID	STUD SIZE RANGE FOR EA. PART No.	STOCK THICKNESS
A-5006-MS	22-18	RED	1.064	.348	.330	.447	.062	.140	6 , 8 , 10	.028
B-5006-MS	16-14	BLUE	1.064	.362	.330	.447	.081	.170	6 , 8 , 10	.031
C-5006-MS	12-10	YELLOW	1.305	.410	.330	.447	.128	.225	6 , 8 , 10	.040