

# SW Series Rocker Switches

## Features/Benefits

- Various designs up to 16 amps
- Heavy duty and extended life cycles
- SPST, SPDT and DPST options
- Different symbols available

## Typical Applications

- Household appliances
- Industrial equipment
- Audio & visual equipment
- Telecommunication
- Office equipment



## Specifications

CONTACT RATING: 6.5 Amps @ 125 VAC  
 ELECTRICAL LIFE: 6,000 cycles at full load.  
 INITIAL CONTACT RESISTANCE: 100m  $\Omega$  min.  
 INSULATION RESISTANCE: 100M  $\Omega$  min.  
 DIELECTRIC STRENGTH: 1,500 VAC (50-60 Hz)  
 OPERATING FORCE: ON\_OFF: 250  $\pm$  100 gf  
 OFF\_ON: 700  $\pm$  250 gf  
 PACKAGING: 300 pieces per bag (5 trays)  
 2,400 pieces per box

## Materials

HOUSING: PA (UL 94V-2).  
 KNOB: PA (UL 94V-2).  
 CONTACTS: Silver plated.

**NOTE:** Specifications and materials listed above are for switches with standard options. For information on specific and custom switches, consult Customer Service Center.

## Environmental

OPERATING TEMPERATURE: 0°C to 65°C

| PART NUMBER             | HOUSING COLOR |
|-------------------------|---------------|
| <b>SW-13A65N-A01</b>    | White         |
| <b>SW-13A65N-A01 BK</b> | Black         |

