



NPN TIP130 – 131 – 132

SILICON DARLINGTON POWER TRANSISTORS

NPN epitaxial-base transistors in a monolithic Darlington circuit and housed in a TO-220 envelope.

They are intended for use in power linear and switching applications.

The complementary PNP types are TIP135/136/137

Compliance to RoHS.

ABSOLUTE MAXIMUM RATINGS

Symbol	Ratings		Value	Unit	
V_{CBO}	Collector-Base Voltage ($I_E = 0$)	TIP130	60	V	
		TIP131	80		
		TIP132	100		
V_{CEO}	Collector-Emitter Voltage ($I_B = 0$)	TIP130	60	V	
		TIP131	80		
		TIP132	100		
V_{EBO}	Emitter-Base Voltage ($I_C = 0$)		5	V	
I_C	Collector Current		8	A	
I_{CM}	Collector Peak Current (1)		12	A	
I_B	Base Current		0.3	A	
P_T	Power Dissipation	T_{case}	@ $T_{mb} < 25^\circ$	70	W
		t_{amb}		2	
t_J	Junction Temperature		150	°C	
t_s	Storage Temperature range		-65 to +150		

THERMAL CHARACTERISTICS

Symbol	Ratings	Value	Unit
R_{thJC}	From Junction to Case Thermal Resistance	1.78	°C/W
R_{thJA}	From Junction to Free-Air Thermal Resistance	62.5	

NPN TIP130 – 131 – 132

ELECTRICAL CHARACTERISTICS

TC=25°C unless otherwise noted


Symbol	Ratings	Test Condition(s)	Min	Typ	Max	Unit	
V_{CEO}	Collector-Emitter Breakdown Voltage (*)	$I_C = 30 \text{ mA}$ $I_B = 0$	TIP130	60	-	-	V
			TIP131	80	-	-	
			TIP132	100	-	-	
I_{CBO}	Collector-Emitter sustaining Current	$V_{CB} = V_{CEO}$ $I_E = 0$	TIP130	-	-	0.2	mA
			TIP131	-	-	0.2	
			TIP132	-	-	0.2	
		$V_{CB} = V_{CEO}$ $I_E = 0$ $T_C = 100^\circ\text{C}$	TIP130	-	-	1	
			TIP131	-	-	1	
			TIP132	-	-	1	
I_{CEO}	Collector-Emitter Cutoff Current	$V_{CE} = 30 \text{ V}$	TIP130	-	-	0.5	A
		$V_{CE} = 40 \text{ V}$	TIP131	-	-	0.5	
		$V_{CE} = 50 \text{ V}$	TIP132	-	-	0.5	
I_{EBO}	Emitter Cutoff Current	$V_{EB} = 5 \text{ V}$ $I_C = 0$	-	-	5	mA	
$V_{CE(SAT)}$	Collector-Emitter saturation Voltage (*)	$I_C = 4 \text{ A}$ $I_B = 16 \text{ mA}$	-	-	2	V	
		$I_C = 6 \text{ A}$ $I_B = 30 \text{ mA}$	-	-	3		
		-	-	-	-		
V_{BE}	Base-Emitter Voltage (*)	$V_{CE} = 4 \text{ V}$ $I_C = 4 \text{ A}$	-	-	2.5	V	
h_{FE}	Forward Current transfer ratio (*)	$V_{CE} = 4 \text{ V}$ $I_C = 1 \text{ A}$	500	-	-	-	
		$V_{CE} = 4 \text{ V}$ $I_C = 4 \text{ A}$	1000	-	1500 0		
C_{OBO}	Output Capacitance	$V_{CB} = 10 \text{ V}$ $I_E = 0$	-	-	200	pF	

(*) Pulse Width $\approx 300 \mu\text{s}$, Duty Cycle $\leq 2.0\%$

NPN TIP130 – 131 – 132

MECHANICAL DATA CASE TO-220

DIMENSIONS (mm)		
	Min.	Max.
A	9,90	10,30
B	15,65	15,90
C	13,20	13,40
D	6,45	6,65
E	4,30	4,50
F	2,70	3,15
G	2,60	3,00
H	15,75	17,15
L	1,15	1,40
M	3,50	3,70
N	-	1,37
P	0,46	0,55
R	2,50	2,70
S	4,98	5,08
T	2,49	2,54
U	0,70	0,90



Pin 1 :	Base
Pin 2 :	Collector
Pin 3 :	Emitter
Case :	Collector

Revised August 2012

Information furnished is believed to be accurate and reliable. However, Comset Semiconductors assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. Data are subject to change without notice. Comset Semiconductors makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does Comset Semiconductors assume any liability arising out of the application or use of any product and specifically disclaims any and all liability, including without limitation consequential or incidental damages. Comset Semiconductors' products are not authorized for use as critical components in life support devices or systems.