



PNP BD912

POWER LINEAR AND SWITCHING APPLICATIONS.

The BD912 are PNP transistors mounted in Jedec TO-220 plastic package. They are intended for use in power linear and switching applications. NPN complements are BD911. Compliance to RoHS.

ABSOLUTE MAXIMUM RATINGS

Symbol	Ratings	Value	Unit
V_{CEO}	Collector-Emitter Voltage	-100	V
V_{CBO}	Collector-Base Voltage	-100	V
V_{EBO}	Emitter-Base Voltage	-5.0	V
I_C	Collector Current	-15	A
I_E	Emitter Current	-15	A
I_B	Base Current	-5	A
P_D	Total Device Dissipation @ $T_C = 25^\circ$	90	W
T_J	Junction Temperature	150	$^\circ\text{C}$
T_{Stg}	Storage Temperature range	-65 to +150	$^\circ\text{C}$

THERMAL CHARACTERISTICS

Symbol	Ratings	Value	Unit
$R_{thJ-case}$	Thermal Resistance, Junction - Case	70	K/W

PNP BD912

ELECTRICAL CHARACTERISTICS

TC=25°C unless otherwise noted

Symbol	Ratings	Test Condition(s)	Min	Typ	Max	Unit
I_{CEO}	Collector Cutoff Current	$-V_{CE}=50\text{ V}, I_B=0$	-	-	-1	mA
I_{CBO}	Collector Cutoff Current	$-V_{CB}=100\text{ V}, I_E=0$	-	-	-0.5	mA
		$-V_{CB}=100\text{ V}, I_E=0, T_j=150^\circ\text{C}$			-5	
I_{EBO}	Emitter Cutoff Current	$-V_{BE}=5\text{ V}, I_C=0$	-	-	-1	mA
V_{CEO}	Collector Emitter Breakdown Voltage	$I_C=10\text{ m A}, I_B=0$	-100	-	-	V
V_{BE}	Base Emitter Voltage (*)	$-I_C=5\text{ A}, -V_{CE}=4\text{ V}$	-	-	-1.5	V
h_{FE}	DC Current Gain (*)	$-I_C=0.5\text{ A}, -V_{CE}=4\text{ V}$	40	-	250	-
		$-I_C=5\text{ A}, -V_{CE}=4\text{ V}$	15	-	-150	
		$-I_C=10\text{ A}, -V_{CE}=4\text{ V}$	5	-	-	
$-V_{CE(SAT)}$	Collector-Emitter saturation Voltage (*)	$-I_C=5\text{ A}, -I_B=0.5\text{ A}$	-	-	1	V
		$-I_C=10\text{ A}, -I_B=2.5\text{ A}$	-	-	3	
$-V_{BE(SAT)}$	Base-Emitter saturation Voltage (*)	$-I_C=10\text{ A}, -I_B=2.5\text{ A}$	-	-	2.5	
f_T	Transition frequency	$-I_C=0.5\text{ A}, -V_{CE}=4\text{ V}$	3	-	-	MHz


(*) Pulse conditions : $t_p < 300\ \mu\text{s}, \delta = 1.5\%$



PNP BD912

MECHANICAL DATA CASE TO-220

DIMENSIONS (mm)		
	Min.	Max.
A	9,90	10,30
B	15,65	15,90
C	13,20	13,40
D	6,45	6,65
E	4,30	4,50
F	2,70	3,15
G	2,60	3,00
H	15,75	17,15
L	1,15	1,40
M	3,50	3,70
N	-	1,37
P	0,46	0,55
R	2,50	2,70
S	4,98	5,08
T	2,49	2,54
U	0,70	0,90



Pin 1 :	Base
Pin 2 :	Collector
Pin 3 :	Emitter
Case :	Collector

Revised September 2012

Information furnished is believed to be accurate and reliable. However, Comset Semiconductors assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. Data are subject to change without notice. Comset Semiconductors makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does Comset Semiconductors assume any liability arising out of the application or use of any product and specifically disclaims any and all liability, including without limitation consequential or incidental damages. Comset Semiconductors' products are not authorized for use as critical components in life support devices or systems.