



# STB55NF06, STP55NF06, STP55NF06FP

N-channel 60 V, 0.015  $\Omega$ , 50 A STripFET™ II Power MOSFET in D<sup>2</sup>PAK, TO-220 and TO-220FP packages


Datasheet — production data

## Features

| Order code  | V <sub>DSS</sub> | R <sub>DS(on)</sub> max. | I <sub>D</sub>      |
|-------------|------------------|--------------------------|---------------------|
| STB55NF06   | 60 V             | < 0.018 $\Omega$         | 50 A                |
| STP55NF06   |                  |                          | 50 A <sup>(1)</sup> |
| STP55NF06FP |                  |                          |                     |

1. Refer to soa for the max allowable current value on FP-type due to R<sub>th</sub> value

- 100% avalanche tested
- Exceptional dv/dt capability




## Applications

- Switching application

## Description

These Power MOSFETs have been developed using STMicroelectronics' unique STripFET process, which is specifically designed to minimize input capacitance and gate charge. This renders the devices suitable for use as primary switch in advanced high-efficiency isolated DC-DC converters for telecom and computer applications, and applications with low gate charge driving requirements.

Figure 1. Internal schematic diagram



AM01475v1

Table 1. Device summary

| Order code  | Marking   | Package            | Packaging     |
|-------------|-----------|--------------------|---------------|
| STB55NF06   | B55NF06   | D <sup>2</sup> PAK | Tape and reel |
| STP55NF06   | P55NF06   | TO-220             | Tube          |
| STP55NF06FP | P55NF06FP | TO-220             |               |

## Contents

|          |                                     |           |
|----------|-------------------------------------|-----------|
| <b>1</b> | <b>Electrical ratings</b>           | <b>3</b>  |
| <b>2</b> | <b>Electrical characteristics</b>   | <b>4</b>  |
| 2.1      | Electrical characteristics (curves) | 6         |
| <b>3</b> | <b>Test circuit</b>                 | <b>9</b>  |
| <b>4</b> | <b>Package mechanical data</b>      | <b>10</b> |
| <b>5</b> | <b>Packaging mechanical data</b>    | <b>16</b> |
| <b>6</b> | <b>Revision history</b>             | <b>18</b> |

# 1 Electrical ratings

**Table 2. Absolute maximum ratings**

| Symbol                         | Parameter   | Value                         |                    | Unit |
|--------------------------------|---|-------------------------------|--------------------|------|
|                                |   | TO-220,<br>D <sup>2</sup> PAK | TO-220FP           |      |
| V <sub>DS</sub>                | Drain-source voltage                                  | 60                            |                    | V    |
| V <sub>GS</sub>                | Gate- source voltage                                  | ± 20                          |                    | V    |
| I <sub>D</sub>                 | Drain current (continuous) at T <sub>C</sub> = 25 °C  | 50                            | 50 <sup>(1)</sup>  | A    |
| I <sub>D</sub>                 | Drain current (continuous) at T <sub>C</sub> = 100 °C | 35                            | 35 <sup>(1)</sup>  | A    |
| I <sub>DM</sub> <sup>(2)</sup> | Drain current (pulsed)                                | 200                           | 200 <sup>(1)</sup> | A    |
| P <sub>tot</sub>               | Total dissipation at T <sub>C</sub> = 25 °C           | 110                           | 30                 | W    |
|                                | Derating factor                                       | 0.73                          | 0.20               | W/°C |
| E <sub>AS</sub> <sup>(3)</sup> | Single pulse avalanche energy                         | 340                           |                    | mJ   |
| dv/dt <sup>(4)</sup>           | Peak diode recovery voltage slope                     | 7                             |                    | V/ns |
| V <sub>ISO</sub>               | Insulation withstand voltage (DC)                     |                               | 2500               | V    |
| T <sub>stg</sub>               | Storage temperature                                   | -55 to 175                    |                    | °C   |
| T <sub>j</sub>                 | Max. operating junction temperature                   |                               |                    |      |

1. Refer to soa for the max allowable current value on FP-type due to R<sub>th</sub> value
2. Pulse width limited by safe operating area.
3. Starting T<sub>j</sub> = 25 °C, V<sub>DD</sub> = 30 V, I<sub>D</sub> = 25 A
4. I<sub>SD</sub> ≤ 50 A, di/dt ≤ 400 A/μs, V<sub>DD</sub> ≤ V<sub>(BR)DSS</sub>, T<sub>j</sub> ≤ T<sub>JMAX</sub>

**Table 3. Thermal data**

| Symbol                | Parameter                               | Value              |        |          | Unit |
|-----------------------|---|--------------------|--------|----------|------|
|                       |   | D <sup>2</sup> PAK | TO-220 | TO-220FP |      |
| R <sub>thj-case</sub> | Thermal resistance junction-case max    | 1.36               | 5      |          | °C/W |
| R <sub>thj-amb</sub>  | Thermal resistance junction-ambient max | 62.5               |        |          | °C/W |

## 2 Electrical characteristics

( $T_{CASE}=25^\circ\text{C}$  unless otherwise specified)

**Table 4. On/off states**

| Symbol              | Parameter  | Test conditions   | Min. | Typ.  | Max.      | Unit                           |
|---------------------|--|---|------|-------|-----------|--------------------------------|
| $V_{(BR)DSS}$       | Drain-source breakdown voltage                   | $I_D = 250 \mu\text{A}, V_{GS} = 0$   | 60   |       |           | V                              |
| $I_{DSS}$           | Zero gate voltage drain current ( $V_{GS} = 0$ ) | $V_{DS} = 60 \text{ V}$<br>$V_{DS} = 60 \text{ V}, @ T_J = 125^\circ\text{C}$ |      |       | 1<br>10   | $\mu\text{A}$<br>$\mu\text{A}$ |
| $I_{GSS}$           | Gate-body leakage current ( $V_{DS} = 0$ )       | $V_{GS} = \pm 20 \text{ V}$   |      |       | $\pm 100$ | nA                             |
| $V_{GS(\text{th})}$ | Gate threshold voltage                           | $V_{DS} = V_{GS}, I_D = 250 \mu\text{A}$                                      | 2    | 3     | 4         | V                              |
| $R_{DS(\text{on})}$ | Static drain-source on-resistance                | $V_{GS} = 10 \text{ V}, I_D = 27.5 \text{ A}$                                 |      | 0.015 | 0.018     | $\Omega$                       |

**Table 5. Dynamic**

| Symbol  | Parameter   | Test conditions  | Min. | Typ.                 | Max. | Unit                 |
|---|---|--|------|----------------------|------|----------------------|
| $C_{iss}$<br>$C_{oss}$<br>$C_{rss}$           | Input capacitance<br>Output capacitance<br>Reverse transfer capacitance | $V_{DS} = 25 \text{ V}, f = 1\text{MHz},$<br>$V_{GS} = 0$  | -    | 1300<br>300<br>105   |      | pF<br>pF<br>pF       |
| $t_{d(on)}$<br>$t_r$<br>$t_{d(off)}$<br>$t_f$ | Turn-on delay time<br>Rise time<br>Turn-off delay time<br>Fall time     | $V_{DD} = 30 \text{ V}, I_D = 27.5 \text{ A}$<br>$R_G = 4.7 \Omega, V_{GS} = 10 \text{ V}$<br>(see <a href="#">Figure 15</a> ) | -    | 20<br>50<br>36<br>15 |      | ns<br>ns<br>ns<br>ns |
| $Q_g$<br>$Q_{gs}$<br>$Q_{gd}$                 | Total gate charge<br>Gate-source charge<br>Gate-drain charge            | $V_{DD} = 48 \text{ V}, I_D = 55 \text{ A},$<br>$V_{GS} = 10 \text{ V}$<br>(see <a href="#">Figure 16</a> )                    | -    | 44.5<br>10.5<br>17.5 | 60   | nC<br>nC<br>nC       |


**Table 6. Source drain diode**

| Symbol                            | Parameter  | Test conditions  | Min. | Typ.             | Max.      | Unit          |
|-----------------------------------|--|--|------|------------------|-----------|---------------|
| $I_{SD}$<br>$I_{SDM}^{(1)}$       | Source-drain current<br>Source-drain current (pulsed)                        |  | -    |                  | 50<br>200 | A<br>A        |
| $V_{SD}^{(2)}$                    | Forward on voltage   | $I_{SD} = 50 \text{ A}, V_{GS} = 0$  | -    |                  | 1.5       | V             |
| $t_{rr}$<br>$Q_{rr}$<br>$I_{RRM}$ | Reverse recovery time<br>Reverse recovery charge<br>Reverse recovery current | $I_{SD} = 50 \text{ A},$<br>$dI/dt = 100 \text{ A}/\mu\text{s},$<br>$V_{DD} = 30 \text{ V}, T_j = 150^\circ\text{C}$<br>(see <a href="#">Figure 17</a> ) | -    | 75<br>170<br>4.5 |           | ns<br>nC<br>A |


1. Pulse width limited by safe operating area.
2. Pulsed: Pulse duration = 300  $\mu\text{s}$ , duty cycle 1.5%

## 2.1 Electrical characteristics (curves)


**Figure 2.** Safe operating area for TO-220, D<sup>2</sup>PAK




**Figure 3.** Thermal impedance for TO-220, D<sup>2</sup>PAK




**Figure 4.** Safe operating area for TO-220FP




**Figure 5.** Thermal impedance TO-220FP









**Figure 6.** Output characteristics




**Figure 7.** Transfer characteristics




**Figure 8. Transconductance****Figure 9. Static drain-source on-resistance****Figure 10. Gate charge vs gate-source voltage** **Figure 11. Capacitance variations****Figure 12. Normalized gate threshold voltage vs temperature****Figure 13. Normalized on-resistance vs temperature**

**Figure 14. Source-drain diode forward characteristics**




### 3 Test circuit


**Figure 15. Switching times test circuit for resistive load**




**Figure 16. Gate charge test circuit**




**Figure 17. Test circuit for inductive load switching and diode recovery times**




**Figure 18. Unclamped inductive load test circuit**



**Figure 19. Unclamped inductive waveform**



**Figure 20. Switching time waveform**





## 4 Package mechanical data

In order to meet environmental requirements, ST offers these devices in different grades of ECOPACK® packages, depending on their level of environmental compliance. ECOPACK® specifications, grade definitions and product status are available at: [www.st.com](http://www.st.com).  
ECOPACK® is an ST trademark.

**Table 7. D<sup>2</sup>PAK (TO-263) mechanical data**


| Dim. | mm   |      |       |
|------|------|------|-------|
|      | Min. | Typ. | Max.  |
| A    | 4.40 |      | 4.60  |
| A1   | 0.03 |      | 0.23  |
| b    | 0.70 |      | 0.93  |
| b2   | 1.14 |      | 1.70  |
| c    | 0.45 |      | 0.60  |
| c2   | 1.23 |      | 1.36  |
| D    | 8.95 |      | 9.35  |
| D1   | 7.50 |      |       |
| E    | 10   |      | 10.40 |
| E1   | 8.50 |      |       |
| e    |      | 2.54 |       |
| e1   | 4.88 |      | 5.28  |
| H    | 15   |      | 15.85 |
| J1   | 2.49 |      | 2.69  |
| L    | 2.29 |      | 2.79  |
| L1   | 1.27 |      | 1.40  |
| L2   | 1.30 |      | 1.75  |
| R    |      | 0.4  |       |
| V2   | 0°   |      | 8°    |

**Figure 21.** D<sup>2</sup>PAK (TO-263) drawing**Figure 22.** D<sup>2</sup>PAK footprint<sup>(a)</sup>

a. All dimensions are in millimeters

**Table 8.** TO-220 type A mechanical data

| Dim. | mm    |       |       |
|------|-------|-------|-------|
|      | Min.  | Typ.  | Max.  |
| A    | 4.40  |       | 4.60  |
| b    | 0.61  |       | 0.88  |
| b1   | 1.14  |       | 1.70  |
| c    | 0.48  |       | 0.70  |
| D    | 15.25 |       | 15.75 |
| D1   |       | 1.27  |       |
| E    | 10    |       | 10.40 |
| e    | 2.40  |       | 2.70  |
| e1   | 4.95  |       | 5.15  |
| F    | 1.23  |       | 1.32  |
| H1   | 6.20  |       | 6.60  |
| J1   | 2.40  |       | 2.72  |
| L    | 13    |       | 14    |
| L1   | 3.50  |       | 3.93  |
| L20  |       | 16.40 |       |
| L30  |       | 28.90 |       |
| ØP   | 3.75  |       | 3.85  |
| Q    | 2.65  |       | 2.95  |


**Figure 23.** TO-220 type A drawing

0015988\_typeA\_Rev\_S

**Table 9.** TO-220FP mechanical data

| Dim. | mm   |      |      |
|------|------|------|------|
|      | Min. | Typ. | Max. |
| A    | 4.4  |      | 4.6  |
| B    | 2.5  |      | 2.7  |
| D    | 2.5  |      | 2.75 |
| E    | 0.45 |      | 0.7  |
| F    | 0.75 |      | 1    |
| F1   | 1.15 |      | 1.70 |
| F2   | 1.15 |      | 1.70 |
| G    | 4.95 |      | 5.2  |
| G1   | 2.4  |      | 2.7  |
| H    | 10   |      | 10.4 |
| L2   |      | 16   |      |
| L3   | 28.6 |      | 30.6 |
| L4   | 9.8  |      | 10.6 |
| L5   | 2.9  |      | 3.6  |
| L6   | 15.9 |      | 16.4 |
| L7   | 9    |      | 9.3  |
| Dia  | 3    |      | 3.2  |



Figure 24. TO-220FP drawing



## 5 Packaging mechanical data

**Table 10. D<sup>2</sup>PAK (TO-263) tape and reel mechanical data**

| Tape |      |      | Reel |          |      |
|------|------|------|------|----------|------|
| Dim. | mm   |      | Dim. | mm       |      |
|      | Min. | Max. |      | Min.     | Max. |
| A0   | 10.5 | 10.7 | A    |          | 330  |
| B0   | 15.7 | 15.9 | B    | 1.5      |      |
| D    | 1.5  | 1.6  | C    | 12.8     | 13.2 |
| D1   | 1.59 | 1.61 | D    | 20.2     |      |
| E    | 1.65 | 1.85 | G    | 24.4     | 26.4 |
| F    | 11.4 | 11.6 | N    | 100      |      |
| K0   | 4.8  | 5.0  | T    |          | 30.4 |
| P0   | 3.9  | 4.1  |      |          |      |
| P1   | 11.9 | 12.1 |      | Base qty | 1000 |
| P2   | 1.9  | 2.1  |      | Bulk qty | 1000 |
| R    | 50   |      |      |          |      |
| T    | 0.25 | 0.35 |      |          |      |
| W    | 23.7 | 24.3 |      |          |      |

**Figure 25. Tape****Figure 26. Reel**

## 6 Revision history

**Table 11. Document revision history**

| Date        | Revision | Changes  |
|-------------|----------|--|
| 19-Oct-2005 | 7        | Preliminary document   |
| 02-Dec-2005 | 8        | New datasheet according to PCN MLD-PMT/05/1115   |
| 28-Mar-2006 | 9        | Inserted ecopack indication  |
| 26-Jun-2006 | 10       | New template, no content change  |
| 25-May-2012 | 11       | Removed part number STB55NF06-1 in I <sup>2</sup> PAK package<br><i>Section 4: Package mechanical data</i> and <i>Section 5: Packaging mechanical data</i> have been updated<br>Minor text changes |

**Please Read Carefully:**

Information in this document is provided solely in connection with ST products. STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, modifications or improvements, to this document, and the products and services described herein at any time, without notice.

All ST products are sold pursuant to ST's terms and conditions of sale.

Purchasers are solely responsible for the choice, selection and use of the ST products and services described herein, and ST assumes no liability whatsoever relating to the choice, selection or use of the ST products and services described herein.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted under this document. If any part of this document refers to any third party products or services it shall not be deemed a license grant by ST for the use of such third party products or services, or any intellectual property contained therein or considered as a warranty covering the use in any manner whatsoever of such third party products or services or any intellectual property contained therein.

**UNLESS OTHERWISE SET FORTH IN ST'S TERMS AND CONDITIONS OF SALE ST DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY WITH RESPECT TO THE USE AND/OR SALE OF ST PRODUCTS INCLUDING WITHOUT LIMITATION IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION), OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT.**

**UNLESS EXPRESSLY APPROVED IN WRITING BY TWO AUTHORIZED ST REPRESENTATIVES, ST PRODUCTS ARE NOT RECOMMENDED, AUTHORIZED OR WARRANTED FOR USE IN MILITARY, AIR CRAFT, SPACE, LIFE SAVING, OR LIFE SUSTAINING APPLICATIONS, NOR IN PRODUCTS OR SYSTEMS WHERE FAILURE OR MALFUNCTION MAY RESULT IN PERSONAL INJURY, DEATH, OR SEVERE PROPERTY OR ENVIRONMENTAL DAMAGE. ST PRODUCTS WHICH ARE NOT SPECIFIED AS "AUTOMOTIVE GRADE" MAY ONLY BE USED IN AUTOMOTIVE APPLICATIONS AT USER'S OWN RISK.**

Resale of ST products with provisions different from the statements and/or technical features set forth in this document shall immediately void any warranty granted by ST for the ST product or service described herein and shall not create or extend in any manner whatsoever, any liability of ST.

ST and the ST logo are trademarks or registered trademarks of ST in various countries.

Information in this document supersedes and replaces all information previously supplied.

The ST logo is a registered trademark of STMicroelectronics. All other names are the property of their respective owners.

© 2012 STMicroelectronics - All rights reserved

STMicroelectronics group of companies

Australia - Belgium - Brazil - Canada - China - Czech Republic - Finland - France - Germany - Hong Kong - India - Israel - Italy - Japan - Malaysia - Malta - Morocco - Philippines - Singapore - Spain - Sweden - Switzerland - United Kingdom - United States of America

[www.st.com](http://www.st.com)

