



Schottky Diode Gen 2

High Performance Schottky Diode
Low Loss and Soft Recovery
Common Cathode

Part number

DSA 30 C 100 HB



Backside: cathode

Features / Advantages:

- Very low V_f
- Extremely low switching losses
- low I_{rm} values
- Improved thermal behaviour
- High reliability circuit operation
- Low voltage peaks for reduced protection circuits
- Low noise switching

Applications:

- Rectifiers in switch mode power supplies (SMPS)
- Free wheeling diode in low voltage converters

Package:

- Housing: TO-247
- Industry standard outline
- Epoxy meets UL 94V-0
- RoHS compliant


| Symbol | Definition | Conditions | | Ratings | | |
|------------|-------------------------------------|--|------------------------------|------------------------------|------|-----|
| | | min. | typ. | max. | Unit | |
| V_{RRM} | max. repetitive reverse voltage | | | 100 | | V |
| I_R | reverse current | $V_R = 100\text{ V}$ | $T_{VJ} = 25^\circ\text{C}$ | | 0.25 | mA |
| | | $V_R = 100\text{ V}$ | $T_{VJ} = 125^\circ\text{C}$ | | 2.5 | mA |
| V_F | forward voltage | $I_F = 15\text{ A}$ | $T_{VJ} = 25^\circ\text{C}$ | | 0.91 | V |
| | | $I_F = 30\text{ A}$ | | | 1.06 | V |
| | | $I_F = 15\text{ A}$ | $T_{VJ} = 125^\circ\text{C}$ | | 0.72 | V |
| | | $I_F = 30\text{ A}$ | | | 0.90 | V |
| I_{FAV} | average forward current | rectangular | $d = 0.5$ | $T_C = 150^\circ\text{C}$ | | A |
| V_{FO} | threshold voltage | $\left. \begin{array}{l} \text{slope resistance} \\ \text{for power loss calculation only} \end{array} \right\}$ | | $T_{VJ} = 175^\circ\text{C}$ | 0.46 | V |
| r_F | slope resistance | | | | 11.7 | mΩ |
| R_{thJC} | thermal resistance junction to case | | | | 1.75 | K/W |
| T_{VJ} | virtual junction temperature | | | -55 | 175 | °C |
| P_{tot} | total power dissipation | | | | 85 | W |
| I_{FSM} | max. forward surge current | $t = 10\text{ ms}$ (50 Hz), sine | | $T_{VJ} = 45^\circ\text{C}$ | | A |
| C_J | junction capacitance | $V_R = 12\text{ V}; f = 1\text{ MHz}$ | | $T_{VJ} = 25^\circ\text{C}$ | 146 | pF |
| E_{AS} | non-repetitive avalanche energy | $I_{AS} = 5\text{ A}; L = 100\text{ }\mu\text{H}$ | | $T_{VJ} = 25^\circ\text{C}$ | 1.25 | mJ |
| I_{AR} | repetitive avalanche current | $V_A = 1.5 \cdot V_R$ typ.: $f = 10\text{ kHz}$ | | | 0.5 | A |

| Symbol | Definition | Conditions | Ratings | | | |
|---------------|-------------------------------------|-----------------------|---------|------|------|-----|
| | | | min. | typ. | max. | |
| I_{RMS} | RMS current | per pin ¹⁾ | | | 50 | A |
| R_{thCH} | thermal resistance case to heatsink | | | 0.25 | | K/W |
| T_{stg} | storage temperature | | -55 | | 150 | °C |
| Weight | | | | 6 | | g |
| M_D | mounting torque | | 0.8 | | 1.2 | Nm |
| F_c | mounting force with clip | | 20 | | 120 | N |

¹⁾ I_{RMS} is typically limited by: 1. pin-to-chip resistance; or by 2. current capability of the chip.

In case of 1, a common cathode/anode configuration and a non-isolated backside, the whole current capability can be used by connecting the backside.

Product Marking



Part number

D = Diode
 S = Schottky Diode
 A = low VF
 30 = Current Rating [A]
 C = Common Cathode
 100 = Reverse Voltage [V]
 HB = TO-247AD (3)

| Ordering | Part Name | Marking on Product | Delivering Mode | Base Qty | Code Key |
|----------|-----------------|--------------------|-----------------|----------|----------|
| Standard | DSA 30 C 100 HB | DSA30C100HB | Tube | 30 | 505053 |

| Similar Part | Package | Voltage class |
|--------------|----------|---------------|
| DSA30C100QB | TO-3P | 100 |
| DSA30C100PB | TO-220 | 100 |
| DSA30C100PN | TO-220FP | 100 |

Outlines TO-247

