

Rack Mount Intake Blowers HB Series





Features

- Standard 19" rack mount
- Air delivery from more than 50% of their 17" width
- Internal neoprene isolation mounts reduce transmission of vibration to the rack
- Air intake only, to pressurize the rack with filtered air
- Heavy steel construction
- Attractive 19" stainless steel grille included
- 115 VAC, 50/60 Hz. motor is UL recognized, CSA certified, ball bearing type, cooled by incoming air
- Includes permanent filter (replacement filters available below)
- Comes with 6' STJW 3- wire cord
- Control your rack temperature with our <u>economical</u>, <u>compact</u> <u>thermostat</u>
- Optional replacement filters come in a pack of five (5).
- Link here to **photo tables** of each part number.

Accessories

• Filter Coat

	Free Flow Air Running Delivery		RPM	Blower	Ambient Temperature			Replacem
Part No.	(CFM)	Amps	Nominal	Туре	(F)	Units	Height	Filter 5-P
HB2160A	145 / 125	0.7	2500 / 3000	TransverseFlow	-20 to +250	2U	3.50	HB2UFIL1
HB3250A	155 / 200	1.2	2750 / 3000	Double Centrifugal	-20 to +250	3U	5.25	HB3UFIL1
HB4500A	405 / 465	2.5	2750 / 3300	Double Centrifugal	-20 to +250	4U	7.00	HB4UFIL1

Data subject to change without notice.